

PRELIMINARY
NOT FOR
CONSTRUCTION

KING+PARKS MULTI-FAMILY RESIDENCES

PROJECT SITE: NE Martin Luther King Jr. Boulevard & N Rosa Parks Way
OWNER: Portland Community Reinvestment Initiatives Inc. (PCRI)
6329 NE Martin Luther King Jr. Blvd. Portland, Oregon 97211



PROJECT NO. 16-0602
ISSUE DATE 06.23.2017

REVISIONS

SHEET
















MECHANICAL
DETAILS

M6.1

NOT FOR CONSTRUCTION

PRICING SET

© MERRYMAN BARNES ARCHITECTS, INC.

SPLIT SYSTEMS/ HEAT PUMP & AC UNITS												
SYSTEM	TOWNHOUSES		1ST FLOOR/2BA&3BA	2ND FLOOR LOBBY	3RD FLOOR LOBBY	4TH FLOOR LOBBY	OFFICE/HAN	1ST FLOOR LOBBY	ELECT.	COMMUNITY	WATER HEATER RM	ELEV. MACH
INDOOR UNIT MARK NUMBER								 				
TYPE (INDOOR UNIT)	WALL MTD	DUCTED FC	WALL MTD	WALL MTD	WALL MTD	WALL MTD	DUCTED	WALL MTD	WALL MTD	WALL MTD	WALL MTD	WALL MTD
HEATING CAPACITY	9000 BTUH	9000 BTUH	18,000 BTUH	21,500 BTUH	21,500 BTUH	21,500 BTUH	8,500 BTUH	21,500 BTUH	15,000 BTUH	24,000 BTUH	9,000 BTUH	34,200 BTUH
COOLING CAPACITY	9000 BTUH	9000 BTUH	20,000 BTUH	25,400 BTUH	25,400 BTUH	25,400 BTUH	9,000 BTUH	25,400 BTUH	28,000 BTUH	24,000 BTUH	12,000 BTUH	—
CFM (HIGH)	380 CCFM	305 CFM	500 CCFM	640 CCFM	640 CCFM	640 CCFM	305 CFM	640 CCFM	583 CCFM	635 CCFM	380 CFM	920 CFM
WEIGHT	20 #	50 #	35 #	50 #	50 #	50 #	65#	50 #	45 #	35 #	35 #	50#
BASIS OF DESIGN: DAIKIN	FTX09LVJU	FDXS09LVJU	FAQ18PVJU	FTXS24LVJU	FTXS24LVJU	FTXS24LVJU	FDXS09LVJU	FTXS24LVJU	FTKN18NMVJU	FAQ24PVJU	FTXS09LVJU	MITSUBISHI *PKA-A36KA4
OUTDOOR UNIT MARK NUMBER								 				
TYPE (OUTDOOR UNIT)	HEAT PUMP		HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	HEAT PUMP	COOLING ONLY
OUTDOOR COOLING CAPACITY	18,000 BTU/HR		18,000 BTU/HR	21,500 BTUH	21,500 BTUH	21,500 BTUH	8,500 BTUH	21,500 BTUH	15,000 BTUH	24,000 BTUH	9,000 BTUH	34,200 BTUH
OUTDOOR HEATING CAPACITY	18,900 BTU/HR		20,000 BTU/HR	25,400 BTH	25,400 BTH	25,400 BTH	10,000 BTH	25,400 BTH	28,000 BTUH	24,000 BTUH	12,000 BTUH	—
COOLING EFFICIENCY (SEER)	16.5		18.6	20	20	20	15.1	20	20.3	17.6	24.5	14.0
HTG EFFICIENCY (HSPF/COP)	9.5/4.1		12.7 HSPF	10.6/3.6	10.6/3.6	10.6/3.6	10.3/3.28	10.6/3.6	11/3.72	9.1 HPSF	12.5/4.47	—
MAX PIPING LENGTH	82 FT PER UNIT		165 FT	98 FT	98 FT	98 FT	66 FT	98 FT	98 FT	165 FT	98 FT	165 FT
MAX PIPING ELEV. CHANGE	49 FT.		98 FT.	66 FT.	66 FT.	66 FT.	49 FT.	66 FT.	66 FT.	98 FT.	66 FT.	100
OUTDOOR UNIT DESIGN WT.	130 LBS.		150 LBS.	150 LBS.	150 LBS.	150 LBS.	150 LBS.	150 LBS.	150 LBS.	150 LBS.	150 LBS.	165#
PUMPED CONDENSATE	YES — **		YES — **	YES — **	YES — **	YES — **	YES — **	YES — **	YES — **	YES — **	YES — **	YES — **
	2MXS18NMVJU		RZQ18PVJU9	RXS24LVJU	RXS24LVJU	RXS24LVJU	RXS09LVJU	RXS24LVJU	RKN18NMVJU	RZQ24PVJU9	RXS09LVJU	MITSUBISHI * PUY-A36NHA4
BOD: DAIKIN												
ELECTRICAL	208/1		208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1	208/1

** — ROUTE CONDENSATE TO FLOOR DRAIN
*** - PROVIDE ALL UNITS THAT CANNOT BE DRAINED BY GRAVITY WITH A CONDENSATE PUMP. ROUTE CONDENSATE DRAINS FROM EACH UNIT TO FLOOR DRAINS SHOWN ON PLUMBING PLANS. KEEP ALL CONDENSATE DRAINS HIDDEN WITHIN STRUCTURE AS MUCH AS POSSIBLE. COORDINATE ALL CONDENSATE LINES WITH ARCHITECT PRIOR TO INSTALLATION.

EXHAUST FANS

MARK NUMBER										
TYPE	CEILING DIRECT DRIVE	CEILING CABINET—**	CEILING CABINET—**	CABINET DIRECT DRIVE	CEILING DIRECT DRIVE	CEILING DIRECT DRIVE	CEILING DIRECT DRIVE	CABINT DIRECT DRIVE	ROOF DIRECT DRIVE	CEILING DIRECT DRIVE
SYSTEM	TOWNHOUSE	BATHROOM	BATHROOM	RECYCLING	1ST JAN/TRASH	2ND JAN/TRASH	3RD JAN/TRASH	1ST FL. R.R.	TRASH COMP.	LAUNDRY 104
CFM	60	90	30/90	350	625	625	625	375	500	340
TOTAL SP. (IN H2O)	0.375"	0.20	0.20	0.375"	0.50"	0.50"	0.50"	0.375"	0.50"	0.50"
RPM	670	1062/1146	1062/1146	1315	1006	1006	1006	1320	1448	1070
TIP SPEED (FPM)	---	NA	NA	---	---	---	---	---	---	---
MOTOR POWER (HP OR WATTS)	80 WATTS	11.7	5/11.7	135 W	254 W	254 W	254 W	135 WATTS	1/8 HP	224 WATTS
CONTROLLED BY	CONTINUOUS	***	*	CONTINUOUS	CONTINUOUS	CONTINUOUS	CONTINUOUS	CONTINUOUS	CONTINUOUS	HUMIDISTAT
INTERLOCK WITH		MOTION SENSOR	MOTION SENSOR							2-POS DAMPER
FAN SPEED CONTROLLER	YES	YES	YES	YES	YES	YES	YES	YES	NO	YES
WHEEL TYPE	FC	BI	BI	FC	FC	FC	FC	FC	BI	FC
BACK DRAFT DAMPER	GRAVITY	GRAVITY	GRAVITY	GRAVITY	2-POS CONTROL DAMPER			GRAVITY	2-POS CTRL DMP	GRAVITY
ISOLATION	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER	RUBBER
DESIGN WEIGHT (LBS)	15	25	25	25	35	35	35	25	20	35
MAX. SONES	1.1	0.3/0.6	0.3/0.6	3.0	1.2	1.2	1.2	0.7	8.1	4.0
BASIS OF DESIGN:	GREENHECK SP-B110	PANASONIC FV-05-11VKL1	PANASONIC FV-05-11VKL1	GREENHECK CSP-A390	GREENHECK CSP-A700	GREENHECK CSP-A700	GREENHECK CSP-A700	GREENHECK CSP-A390	GREENHECK G-095-D	GREENHECK SP-A510
VOLTS/PHASE	120/60/1	120/1/60	120/1/60	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1	120/60/1

* — FAN TO RUN AT LOW SPEED CONTINUOUSLY, AND INCREASE TO HIGH SPEED UPON ACTIVATION OF THE MOTION SENSOR.
** — FANS TO INCLUDE MOTION SENSOR AND MULTI SPEED CONTROL WITH TIME DELAY.
***- FAN TO OPERATE UPON ACTIVATION OF THE MOTION SENSOR.

ELECTRIC WALL HEATER

MARK NUMBER					
TYPE	RECESSED/WALL MTD	RECESSED/WALL MTD	RECESSED/WALL MTD	RECESSED/WALL MTD	RECESSED/WALL MTD
SYSTEM	BEDROOM	STAIR 3	STAIR 4	LAUNDRY 2	LAUNDRY 104
VOLTS/PHASE	120/1	208/1	208/1	208/1	208/1
ELECT HEAT KW	1.5 KW	2.0 KW	2.0 KW	2.0 KW	2.0 KW
BASIS OF DESIGN—BERKO	SRA1512DSF	SRA2020DSF	SRA2020DSF	SRA2020DSF	SRA2020DSF
NOTES:	1	1,2	1,2	1,2	3

NOTES:
1. PROVIDE TAMPER-PROOF THERMOSTAT, WALL CAN, AND GRILL
2. INSTALL ON MIDLAND BETWEEN 1ST AND 2ND FLOORS.
3. SET TO 50°F (ADJUSTABLE).

INDOOR UNITS — **

MARK NUMBER		
SYSTEM GROUND FLOOR	COMMUNITY	OFFICE
TYPE	DUCTED	DUCTED
EFFICIENCY	SEE OUTDOOR UNIT	SEE OUTDOOR UNIT
NOMINAL COOLING CAPACITY	36,000 BTUH	24,000 BTUH
HEATING CAPACITY	27,300 BTUH/8 KW ELECT	20,500 BTUH/6 KW ELECT
TOTAL SUPPLY CFM	1200	800
OSA CFM	260	45
EXTERNAL SP. ("H2O)	0.25	0.25
VOLTS/PHASE	208/1	208/1
MCA/MOP	40 MCA/40 MOP	29 MCA/30 MOP
WEIGHT	30	30
BASIS OF DESIGN	FIRST CO 36HX8-C	FIRST CO 25HX6-C
OUTDOOR UNIT		

* — INDOOR UNIT REQUIRES A SEPARATE CONNECTION, SEE WIRING DIAGRAM ON EQUIPMENT CUT SHEET FOR WIRING & PROTECTION DETAILS.

*** - PROVIDE ALL UNITS THAT CANNOT BE DRAINED BY GRAVITY WITH A CONDENSATE PUMP. ROUTE CONDENSATE DRAINS FROM EACH UNIT TO FLOOR DRAINS SHOWN ON PLUMBING PLANS. KEEP ALL CONDENSATE DRAINS HIDDEN WITHIN STRUCTURE AS MUCH AS POSSIBLE. COORDINATE ALL CONDENSATE LINES WITH ARCHITECT PRIOR TO INSTALLATION.

OUTDOOR UNITS — SPLIT SYSTEM HEAT PUMP

MARK NUMBER		
SYSTEM	COMMUNITY	OFFICE
TYPE	HEAT PUMP	HEAT PUMP
NORMAL COOLING CAPACITY	36,000 BTUH	24,000 BTUH
NORMAL HEATING CAPACITY	36,000 BTUH	24,900 BTUH
EFFICIENCY SEER/EER	14.0/11.5	14.0/11.5
EFFICIENCY HSPF/COP	8.2/3.84	8.2/3.84
REFRIGERANT	410 A	410 A
MAX OPERATING TEMPS	115/5	115/5
MAX PIPING LENGTH	200 FT	200 FT
MAX PIPING HEIGHT	80 FT	80 FT
VOLTS-PHASE	208/1	208/1
MCA/MOP	18/30 AMPS	11/15 AMPS
COMPRESSOR	CONSTANT SPEED	CONSTANT SPEED
WEIGHT	270 LBS	250 LBS
BASIS OF DESIGN	TRANE 4TWB4036G1000B	TRANE 4TWB4024G1000B

MERRIMAN BARNES ARCHITECTS
Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0677
CONTACT: Takako Baker