

IN THE EVENT CONFLICTS ARE DISCOVERED
BETWEEN THE ORIGINAL SIGNED AND SEALED
DOCUMENTS PREPARED BY THE ARCHITECTS
AND/OR THEIR CONSULTANTS, AND ANY COPY OF
THE DOCUMENTS TRANSMITTED BY MAIL, FAX,
ELECTRONICALLY OR OTHERWISE, THE ORIGINAL
SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E1.00

MFA
Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR

ELECTRICAL SYMBOL LIST

LIGHTING SYMBOLS

	LIGHT FIXTURE, RECESSED
	LIGHT FIXTURE, RECESSED - EMERGENCY
	LIGHT FIXTURE, SURFACE MOUNT
	LIGHT FIXTURE, SURFACE MOUNT - EMERGENCY
	LIGHT FIXTURE, STRIP
	LIGHT FIXTURE, STRIP - EMERGENCY
	DOWNLIGHT FIXTURE, RECESSED
	DOWNLIGHT FIXTURE, RECESSED, WALLWASH
	DOWNLIGHT FIXTURE, RECESSED - EMERGENCY
	LIGHT FIXTURE, WALL MOUNT
	LIGHT FIXTURE, CEILING MOUNT
	RECESSED LIGHT FIXTURE, WALL MOUNT
	LIGHT FIXTURE, WALL MOUNT
	LIGHT FIXTURE, WALL SCONCE
	LIGHT FIXTURE, COVE - RECESSED
	LIGHT FIXTURE, COVE - SURFACE
	LIGHT FIXTURE, UNDER CABINET/SHELF
	EXIT SIGN, UNIVERSAL MOUNT, W/ DIRECTIONAL ARROW
	EXIT SIGN, WALL MOUNT, +8'-0" A.F.F.
	EMERGENCY LIGHT W/ BATTERY PACK, +8'-0" A.F.F.
	FLOOD LIGHT
	AREA LUMINAIRE, POST TOP
	AREA LUMINAIRE, BOLLARD
	AREA LUMINAIRE, WALL MOUNT
	AREA LUMINAIRE, POLE MOUNT

SWITCH SYMBOLS

	SWITCH, SPST +48" A.F.F.
	SWITCH, DPST +48" A.F.F.
	SWITCH, 3-WAY +48" A.F.F.
	SWITCH, 4-WAY +48" A.F.F.
	SWITCH, MOMENTARY +48" A.F.F.
	SWITCH, DIMMER +48" A.F.F.
	SWITCH, SPST, W/PILOT LIGHT +48" A.F.F.
	SWITCH, 3-WAY, W/PILOT LIGHT +48" A.F.F.
	SWITCH, KEY-OPERATED +48" A.F.F.
	SWITCH, TIMED +48" A.F.F.
	EXISTING SWITCH, SPST
	PHOTOCELL CONTROL
	OCCUPANCY SENSOR CONTROL

WIRING SYMBOLS

	PANEL & CIRCUIT NUMBER
	HOMERUN TO PANEL
	CONDUCTOR SIZE (IF OTHER THAN #12)
	PHASE CONDUCTOR
	NEUTRAL CONDUCTOR
	GROUND CONDUCTOR
	CONCEALED CONDUIT
	CONDUIT SIZE
	CONDUIT (UNDER SLAB OR FLOOR)
	FLEXIBLE CONNECTION
	CONDUIT, STUBBED & CAPPED
	NORMAL POWER CIRCUIT LINETYPE
	EMERGENCY POWER CIRCUIT LINETYPE
	EXISTING POWER CIRCUIT LINETYPE

FIRE RATED INSTALLATION NOTE:
ELECTRICAL ITEMS (LIGHT FIXTURES, BOXES, ETC.) WHICH ARE RECESSED INTO FIRE-RATED CEILINGS OR WALLS, SHALL BE "ALCOVED" IN GYPSUM BOARD ENCLOSURES PER ARCHITECTURAL DETAILS, OR THE DEVICES SHALL BE "UL" LISTED WITH FIRE-RATING EQUAL TO OR GREATER THAN THE FIRE-RATING OF THE ADJACENT CONSTRUCTION.

1. SYMBOLS & ABBREVIATIONS MAY OR MAY NOT APPLY TO PROJECT
2. REFER TO LOW VOLTAGE DRAWINGS FOR ASSOCIATED SYMBOLS

POWER SYMBOLS

	RECEPTACLE, SINGLE +18" A.F.F.
	RECEPTACLE, DUPLEX +18" A.F.F.
	RECEPTACLE, QUAD +18" A.F.F.
	RECEPTACLE, DUPLEX +6" ABV COUNTER
	RECEPTACLE, DUPLEX +18" A.F.F. (ONE OUTLET SWITCHED)
	RECEPTACLE, DUPLEX +18" A.F.F. (BOTH OUTLETS SWITCHED)
	RECEPTACLE, DUPLEX, PEDESTAL MOUNT
	RECEPTACLE, DUPLEX, FLUSH FLOOR MOUNT
	RECEPTACLE, SPECIAL (COORDINATE WITH EQUIPMENT SERVED)
	RELAY
	TIME CLOCK CONTROL
	PUSHBUTTON STATION
	JUNCTION BOX
	JUNCTION BOX, EMERGENCY CIRCUIT
	THERMOSTAT
	TRANSFORMER
	DISCONNECT, NON-FUSED
	DISCONNECT, FUSED
	ELECTRICAL CONNECTION
	ELECTRICAL CONNECTION, SINGLE MOTOR
	ELECTRICAL CONNECTION, MULTI-MOTOR
	ELECTRICAL DISTRIBUTION PANEL, RECESSED
	ELECTRICAL DISTRIBUTION PANEL, SURFACE
	MISCELLANEOUS PANEL, RECESSED
	MISCELLANEOUS PANEL, SURFACE
	FLUSH FLOOR BOX (W/ DEVICES AS SHOWN ON PLAN)
	FIRE SMOKE DAMPER

ONE-LINE DIAGRAM SYMBOLS

	ELECTRICAL DISTRIBUTION PANELBOARD (MLO)
	ELECTRICAL DISTRIBUTION PANELBOARD (MCB)
	SUB-FEED CIRCUIT BREAKER
	CIRCUIT BREAKER (TRIP RATING & POLES AS INDICATED ON PLAN)
	MAIN SWITCH (RATING & POLES AS INDICATED ON PLAN)
	FUSE (RATING & CLASS AS INDICATED ON PLAN)
	TRANSFER SWITCH (MANUAL OR AUTOMATIC)
	GENERATOR (RATING AS INDICATED ON PLAN)
	TRANSFORMER (RATING AS INDICATED ON PLAN)
	FUSE (RATING & CLASS AS INDICATED ON PLAN)
	GROUND SYSTEM (SIZE AS INDICATED ON PLAN)
	WATER PIPE GROUND ELECTRODE
	TRANSIENT VOLTAGE SURGE SUPPRESSOR
	UTILITY METER & METER BASE
	UTILITY METER CURRENT TRANSFORMER
	FEEDER NO. (SEE FEEDER SCHEDULE)
	POTENTIAL TRANSFORMER (RATING AS INDICATED ON PLANS)

ABBREVIATIONS

'A'	LIGHT FIXTURE TYPE (SEE FIXTURE LIST)
A.F.F.	ABOVE FINISHED FLOOR
A.F.G.	ABOVE FINAL GRADE
A.F.I.	ARC FAULT INTERRUPTER
A.T.S.	TRANSFER SWITCH, AUTOMATIC
C	CONDUIT
C.O.	CONDUIT ONLY
CATV	CABLE TELEVISION
CB	CIRCUIT BREAKER
CCTV	CLOSED CIRCUIT TELEVISION
C.T.	CURRENT TRANSFORMER
(E)	EXISTING
E.L.	EMERGENCY LIGHT
E.L.C.	EXTERIOR LIGHTING CONTROL
FACP	FIRE ALARM CONTROL PANEL
G.F.I.	GROUND FAULT INTERRUPTER
GND	GROUND
H.I.D.	HIGH INTENSITY DISCHARGE
HP	HORSEPOWER
I.G.	ISOLATED GROUND
I R	INFRARED
JB	JUNCTION BOX
LCP	LIGHTING CONTROL PANEL
MCB	MAIN CIRCUIT BREAKER
MLO	MAIN LUGS ONLY
M.T.S.	TRANSFER SWITCH, MANUAL
(N)	NEW
N.I.C.	NOT IN CONTRACT
N.L.	NIGHT LIGHT
OL	OVERLOAD
O.L.C.	OFFICE LIGHTING CONTROL
P	POLE
P.A.	PUBLIC ADDRESS
PC	PARTIAL CIRCUIT
PH	PHASE
PRI	PRIMARY
R.T.U.	REMOTE TELEMETRY UNIT
SEC	SECONDARY
SCCR	SHORT CIRCUIT CURRENT RATING
T.V.S.S.	TRANSIENT VOLTAGE SURGE SUPPRESSOR
U.G.	UNDERGROUND
U.O.N.	UNLESS OTHERWISE NOTED
VFD	VARIABLE FREQUENCY DRIVE
W	WIRE
W.G.	WIRE GUARD
W.P.	WEATHERPROOF
W.T.	WATERTIGHT
X.P.	EXPLOSION PROOF

NOTATIONS

	DRAWING NOTE
	DETAIL REFERENCE: TOP=DETAIL NO., BOTTOM=SHEET NO.
	MECHANICAL EQUIPMENT MARK NO. (SEE EQUIPMENT SCHEDULE)
	EQUIPMENT NO. (SEE EQUIPMENT SCHEDULE)
	EQUIPMENT NO. (SEE EQUIPMENT SCHEDULE)
	EQUIPMENT NO. (SEE EQUIPMENT SCHEDULE)
	FIXTURE REFERENCE: TOP=TYPE, BOTTOM=LAMP QTY & WATTS

GENERAL CONSTRUCTION NOTES:

CONTRACTOR SHALL BE RESPONSIBLE FOR THOROUGHLY REVIEWING THE PLANS AND SPECIFICATION DOCUMENTS PRIOR TO THE START OF ANY WORK. ANY DISCREPANCIES IN THE PROJECT DOCUMENTS SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT IMMEDIATELY AND PRIOR TO THE START OF ANY WORK.

ALL DIMENSIONS ARE MEASURED TO THE CENTER OF THE DEVICE ABOVE FINISHED FLOOR UNLESS OTHERWISE NOTED AS IS STANDARD BUILDING PRACTICE.

ALL ELECTRICAL PLANS ARE DIAGRAMMATICAL AND THE CONTRACTOR SHALL CONSULT THE ARCHITECTURAL PLANS AND ELEVATIONS FOR EXACT LOCATION AND MOUNTING HEIGHTS OF DEVICES AND FIXTURES.

THE ELECTRICAL CONTRACTOR SHALL REVIEW ALL PROJECT DOCUMENTATION AND COORDINATE WITH ALL OTHER TRADES THROUGHOUT THE COURSE OF THE PROJECT.

ALL WORK SHALL BE IN ACCORDANCE WITH ALL NATIONAL, STATE AND LOCAL CODES. CONTRACTOR SHALL BE RESPONSIBLE TO BE INFORMED OF ALL SUCH CODES AS THEY APPLY TO THE SCOPE OF THE PROJECT.

GENERAL NOTES:

- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL AND MAY NOT ACCURATELY REFLECT ACTUAL CONSTRUCTION CONDITIONS. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL ELECTRICAL EQUIPMENT, WITH ALL TRADES PRIOR TO AND DURING CONSTRUCTION.
- ALL WORK SHALL BE DONE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE & NATIONAL CODES.
- CONTRACTOR SHALL REVIEW THE DIVISION 26 SPECIFICATIONS AND THE ENTIRE DRAWING PACKAGE FOR THIS PROJECT PRIOR TO THE START OF ANY WORK.
- THE ELECTRICAL CONTRACTOR SHALL CONSULT WITH ALL OTHER TRADES AND PROVIDE THE APPROPRIATE POWER CONNECTION(S) AND COORDINATE EXACT LOCATIONS PRIOR TO ROUGH IN.
- THE ELECTRICAL CONTRACTOR SHALL IMMEDIATELY ADVISE THE ARCHITECT OF ANY DISCREPANCIES DISCOVERED WITHIN THE DOCUMENTS.
- ALL PRODUCT SUBMITTALS AND SUBSTITUTIONS SHALL BE PROVIDED TO THE ARCHITECT FOR REVIEW AND APPROVAL PRIOR TO PLACING ANY ORDERS.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR ALL MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES.
- REFER TO INTERIOR DECORATOR AND/OR ARCHITECTURAL DRAWINGS FOR EXACT LOCATION(S) AND ELEVATIONS FOR FIXTURES & DEVICES.
- ELECTRICAL CONTRACTOR SHALL CONSULT ARCHITECTURAL AND INTERIOR DECORATOR'S PLAN DOCUMENTS SUCH AS INTERIOR ELEVATIONS, REFLECTED CEILING PLANS, ETC., FOR FIXTURE AND DEVICE DIMENSIONS NOT OTHERWISE NOTED ON THE ELECTRICAL PLANS.

GENERAL POWER NOTES:

- ELECTRICAL PANELS LOCATED IN PUBLIC OR UNSECURED SPACES SHALL BE PROVIDED WITH A LOCKABLE DOOR PANEL.
- SERVICE ENTRANCE AND METERING EQUIPMENT SHOWN TO APPROXIMATE SCALE, BASED ON INDUSTRY STANDARD PRODUCTS. ELECTRICAL CONTRACTOR SHALL ENSURE THAT ALL EQUIPMENT WILL FIT THE SPACE AND MAINTAIN REQUIRED WORKING CLEARANCES.
- COORDINATE WITH LOCAL UTILITY PROVIDER FOR EXACT SERVICE CONDUIT AND CONDUCTORS REQUIREMENTS.
- ALL UTILITY WORK SHALL BE DONE IN ACCORDANCE WITH PGE ELECTRICAL SERVICE REQUIREMENTS.
- THERE SHALL BE NO SURFACE MOUNTED DEVICES OR PATHWAYS (CONDUIT, ETC.) IN ANY PUBLICLY ACCESSIBLE SPACES, INCLUDING STAIRWELLS AND EXIT PASSAGEWAYS WITHOUT PRIOR APPROVAL BY OWNER AND ARCHITECT. ROUTE ALL PATHWAYS WITHIN STUD CAVITIES OR ABOVE FINISHED CEILINGS.
- ELECTRICAL CONTRACTOR TO PROVIDE THERMOSTATS NOT SUPPLIED BY MECHANICAL CONTRACTOR. CONSULT MECHANICAL PLANS FOR ADDITIONAL INFORMATION.
- ELECTRICAL CONTRACTOR SHALL PROVIDE INSTALLATION AND FINAL CONNECTION OF THERMOSTATS. CONSULT MECHANICAL CONTRACTOR FOR EXACT REQUIREMENTS PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE ("T" SERIES) PLANS, INCLUDING FIRE ALARM AND SYSTEMS INSTALLER, AND PROVIDE ROUGH IN AS NEEDED.

GENERAL LIGHTING NOTES:

- REFER TO SHEET E1.21 & E1.22 FOR LIGHT FIXTURE SCHEDULES.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS, ALL MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES.
- REFER TO AVAILABLE ARCHITECTURAL AND/OR INTERIOR DESIGN DOCUMENTS & DRAWINGS FOR ADDITIONAL INFORMATION.
- OCCUPANCY SENSORS SHALL BE FIELD ADJUSTED TO ENSURE COVERAGE AND PROPER CONTROL.
- PROVIDE DIGITAL LIGHTING CONTROLS FOR EACH ROOM/SPACE, CONSISTING OF MULTI-BUTTON SWITCH(ES), OCC SENSORS, LIGHTING PACKS, DAYLIGHT SENSORS, DIMMERS, INTERCONNECTING WIRING, ETC.
- CORRIDOR LIGHTING TO BE CONSTANT "ON" AND PROVIDED WITH LOCAL MANUAL OVERRIDE SWITCHES FOR MAINTENANCE. REFER TO SHEET E1.22 FOR SWITCH WIRING DIAGRAMS.
- REFER TO SHEET E1.23 FOR LIGHTING CONTROL DIAGRAMS AND DESIGN INTENT. VERIFY LIGHTING CONTROLLABILITY WITH ARCHITECT AND/OR OWNER'S REPRESENTATIVE TO DETERMINE EXACT NEEDS FOR ALL PUBLIC/Common AREAS SUCH AS LOBBIES, OFFICES, LOUNGE AREAS, ETC., PRIOR TO THE START OF ANY WORK.
- ALL EGRESS FIXTURES SHALL BE WIRED SUCH THAT IN THE EVENT OF A LIGHTING FAILURE, ALL LIGHTS WILL AUTOMATICALLY RETURN TO FULL LIGHTING. REFER TO SWITCHING DETAILS ON SHEET E1.22.



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED
BETWEEN THE ORIGINAL SIGNED AND SEALED
DOCUMENTS PREPARED BY THE ARCHITECTS
AND/OR THEIR CONSULTANTS, AND ANY COPY OF
THE DOCUMENTS TRANSMITTED BY MAIL, FAX,
ELECTRONICALLY OR OTHERWISE, THE ORIGINAL
SIGNED AND SEALED DOCUMENTS SHALL GOVERN.



PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E1.01



1
E1.01 SITE ELECTRICAL PLAN
SCALE: 1/16" = 1'-0"

GENERAL NOTES:

- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND NATIONAL CODES.
- ELECTRICAL PLANS ARE DIAGRAMMATIC AND MAY OR MAY NOT REFLECT ACTUAL FIELD CONDITIONS.
- REFER TO LIGHTING PLANS FOR BUILDING MOUNTED LIGHT FIXTURE LOCATIONS.
- COORDINATE WITH LOCAL UTILITY PROVIDER FOR EXACT SERVICE CONDUIT AND CONDUCTORS REQUIREMENTS.
- ALL UTILITY WORK SHALL BE DONE IN ACCORDANCE WITH CLARK PUBLIC UTILITIES ELECTRICAL SERVICE REQUIREMENTS.
- U.G. PRIMARY FEEDER SHALL HAVE A MINIMUM 48 INCH BURY.
- U.G. SECONDARY FEEDER SHALL HAVE A MINIMUM 36 INCH BURY.
- REFER TO SHEET E1.11 FOR ONE-LINE DIAGRAM, LOAD SUMMARY INFORMATION AND TYPICAL FEEDER SCHEDULE.
- SECONDARY CONDUIT SWEEPS SHALL BE MINIMUM 60 INCH RADIUS WITH A MINIMUM OF 7'-0" STRAIGHT CONDUIT RUN BETWEEN SWEEPS.
- CONTRACTOR SHALL REVIEW THE UTILITY PROVIDER'S ELECTRICAL SERVICE REQUIREMENTS PRIOR TO THE START OF ANY WORK.
- LOCATION AND INSTALLATION OF THE PRIMARY AND SECONDARY CONDUITS, TRANSFORMER, ETC. SHALL BE PROVIDED PER UTILITY PROVIDER'S ELECTRICAL SERVICE REQUIREMENTS.
- CONTRACTOR SHALL REVIEW ALL PROJECT DOCUMENTS AND SPECIFICATIONS IN DETAIL AND REFER TO THE DOCUMENTS THROUGHOUT THE CONSTRUCTION.
- CONTRACTOR TO LOCATE ALL UNDERGROUND UTILITIES BEFORE TRENCHING.

KEYED POWER NOTES:

UTILITY REQUIREMENTS

- CUSTOMER TO PROVIDE ALL TRENCHING AND BACKFILLING. TRENCH TO BE 36 INCHES DEEP AND 30 INCHES WIDE, MEASURED FROM FINAL GRADE.
- ALL UTILITY CONDUCTORS TO BE INSTALLED IN GRAY SCHEDULE 40, ELECTRICAL GRADE, PVC CONDUIT WITH NYLON PULL STRINGS (MIN 500 LBS. TEST). CLARK PUBLIC UTILITIES TO DETERMINE THE SIZE AND NUMBER OF CONDUITS REQUIRED. ALL ELBOWS TO BE 36 INCH (MIN) RADIUS. ALL BENDS MAY BE FACTORY MADE. IF MORE THAN 270 DEGREES OF BENDS OR IF RUN IS LONGER THAN 150 FEET, BENDS MUST BE RIGID STEEL.
- CONSULT WITH UTILITY REPRESENTATIVE 2 WEEKS BEFORE STARTING MAIN POWER TRENCHING FOR A PRE-CONSTRUCTION CONFERENCE. INCLUDED IN THIS CONFERENCE WILL BE EXCAVATOR, CPU, TELCO, CATV, AND GAS.
- ELECTRICAL UTILITY PROVIDER:
CLARK PUBLIC UTILITIES
CONSTRUCTION SERVICES
360.992.8558

INCOMING ELECTRICAL SERVICE DIVISION OF RESPONSIBILITY					
ELEC. CONTR.	UTILITY CO.		ELEC. CONTR.	UTILITY CO.	
PRIMARY CONDUIT	<input checked="" type="checkbox"/>		SECONDARY CONDUIT	<input checked="" type="checkbox"/>	
PRIMARY CONDUCTORS	<input checked="" type="checkbox"/>		SECONDARY CONDUCTORS	<input checked="" type="checkbox"/>	
TRANSFORMER	<input checked="" type="checkbox"/>		OT ENCLOSURE	<input checked="" type="checkbox"/>	
TRANSFORMER PAD	<input checked="" type="checkbox"/>		OT's	<input checked="" type="checkbox"/>	
PRIMARY GROUNDING	<input checked="" type="checkbox"/>		METER BASE	<input checked="" type="checkbox"/>	
BOLLARDS	<input checked="" type="checkbox"/>		METER	<input checked="" type="checkbox"/>	
TRANSFORMER CONNECTIONS	<input checked="" type="checkbox"/>		METER GROUNDING	<input checked="" type="checkbox"/>	
ELECTRIC ROOM DOOR	<input checked="" type="checkbox"/>				
LOCK BOX (OBTAIN FROM POWER COMPANY)	<input checked="" type="checkbox"/>				

- NOTES:
- CONTACT AND COORDINATE ALL REQUIREMENTS AND RESPONSIBILITIES WITH SERVING UTILITY COMPANIES PRIOR TO SUBMITTING BID.
 - ALL SERVICE INSTALLATION WORK SHALL BE IN STRICT COMPLIANCE WITH THE REQUIREMENTS OF THE SERVING UTILITIES.

POWER UTILITY CONTACT:	TELEPHONE UTILITY CONTACT:	CABLE TV UTILITY CONTACT:
CHARLIE BEATTY CLARK PUBLIC UTILITIES OFFICE (360) 992-8721 CELL (360) 395-0281 EMAIL: CBEATTY@CLARK PUD.COM	MANDY STUBBLEFIELD CENTURYLINK PHONE: MANDY.STUBBLE EMAIL: FIELD@CENTURY LINK.COM	BOB MILLAR COMCAST PHONE: (360) 316-1128 EMAIL: BOB.MILLAR@CO MCAST.COM

INTERFACE ENGINEERING, INC. HAS CONTACTED THE UTILITIES BUT HAS NOT RECEIVED IN WRITING THE FINAL REQUIREMENTS FROM CLARK PUBLIC UTILITIES, CENTURYLINK, COMCAST. THESE DRAWINGS INDICATE OUR BEST ESTIMATION OF THEIR REQUIREMENTS. PRIOR TO BID AND PRIOR TO ANY CONSTRUCTION CONTACT THE UTILITIES AND OBTAIN IN WRITING THEIR REQUIREMENTS.


**M
E
I
A**
INC.
Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0677
CONTACT: DENISE TAYLOR

FEEDER SCHEDULE (COPPER)				
NO.	AMPS	CONDUIT	CONDUCTOR	
①		*(8) 4"	PER UTILITY CO.	& (1) GND
②	2000A	*(5) 4"	ea w/ (4) #600Kcmil	& (1) #250Kcmil
③	1200A	*(3) 4"	ea w/ (4) #600Kcmil	& (1) #3/0 GND
④	800A	*(2) 4"	ea w/ (4) #600Kcmil	& (1) #1/0 GND
⑤	600A	*(2) 3"	ea w/ (4) #350Kcmil	& (1) #1 GND
⑥	400A	3 1/2"	(4) #500Kcmil	& (1) #3 GND
⑦	250A	2 1/2"	(4) #250Kcmil	& (1) #4 GND
⑧	200A	2"	(4) #3/0	& (1) #6 GND
⑨	150A	2"	(4) #1/0	& (1) #6 GND
⑩	100A	1 1/2"	(4) #1	& (1) #8 GND
⑪	125A	1 1/2"	(3) #1	& (1) #6 GND
⑫	100A	1 1/2"	(3) #1	& (1) #8 GND


FEEDER SCHEDULE (ALUMINUM)				
NO.	AMPS	CONDUIT	CONDUCTOR	
①		*4"	PER UTILITY CO.	& (1) GND
②	2000A	*(6) 4"	ea w/ (4) #500 MCM	& (1) #250 GND
③	1200A	*(3) 3 1/2"	ea w/ (4) #600 MCM	& (1) #1/0 GND
④	800A	*(2) 3 1/2"	ea w/ (4) #600 MCM	& (1) #1/0 GND
⑤	600A	*(2) 3"	ea w/ (4) #350 MCM	& (1) #1 GND
⑥	400A	3 1/2"	(4) #500 MCM	& (1) #2 GND
⑦	250A	2 1/2"	(4) #250 MCM	& (1) #4 GND
⑧	200A	2"	(4) #3/0	& (1) #6 GND
⑨	150A	2"	(4) #1/0	& (1) #6 GND
⑩	100A	1 1/4"	(4) #2	& (1) #8 GND
⑪	125A	1 1/2"	(3) #1	& (1) #6 GND
⑫	100A	1 1/4"	(3) #2	& (1) #8 GND

* PARALLEL FEEDERS PER UTILITY PROVIDER'S DIRECTION.

- NOTES:
- REFER TO THE UTILITY PROVIDER'S DESIGN AND INCOMING SERVICE DIVISION OF RESPONSIBILITIES FOR ADDITIONAL INFORMATION.
 - ALUMINUM CONDUCTORS MAY BE USED IN LIEU OF COPPER FOR SECONDARY FEEDERS.
 - ALUMINUM CONDUCTORS MAY BE USED FOR FEEDERS OVER 100A.
 - USE OF ALUMINUM FEEDERS SHALL BE AS ALLOWED BY THE NEC.



1 ELECTRICAL ONE-LINE DIAGRAM
E1.11 208/120v, 3ph, 4w



2 GROUNDING/BONDING DIAGRAM
E1.11 208/120v, 3ph, 4w

FLEX STATION Main distribution Center "MDP"						
LOAD:	LIGHTS	RECEPT	HEAT	MISC	EQUIP	MOTORS
House Panels (H1 & H2)	22,750	10,440	27,732	0	6,000	17,056
Elevator						43,200
Residential Meters (MC1)				388,000		
Retail Meters (MC2)				62,150		
2072 sf @ 30w/sf						
SUBTOTAL	22,750	10,440	27,732	450,150	6,000	60,256
X-FACTOR	1.25	1 + .5	1	1	1	0.25
CODE LOAD:	28,438	10,220	27,732	450,150	6,000	60,256

CONN LOAD: 621 KVA

VOLTS:	208	3ph
TOTAL CALC:	594	KVA
CALC AMPS:	1648	AMPS

ONE-LINE GENERAL NOTES:

- COORDINATE ALL WORK ASSOCIATED WITH ELECTRIC SERVICE WITH LOCAL UTILITY. PROVIDE ALL CONDUIT, GROUNDING, TRANSFORMER VAULT/PAD, ETC., IN ACCORDANCE WITH SERVING UTILITY REQUIREMENTS.
- COORDINATE METERING REQUIREMENTS WITH UTILITY.
- FOR LOAD CENTER FEEDER LENGTHS GREATER THAN 145'-0" FROM METER CENTER, INCREASE WIRE SIZE ONE SIZE UP FOR VOLTAGE DROP.
- PER NEC 240.87, THE ELECTRICAL CONTRACTOR SHALL PROVIDE DOCUMENTATION FOR ARC ENERGY REDUCTION DEVICE(S) FOR CIRCUIT BREAKERS 1200A OR GREATER. CONTRACTOR SHALL PROVIDE AN ENERGY-REDUCING ACTIVE FLASH MITIGATION SYSTEM OR OTHER METHOD APPROVED BY THE NEC.
- USE OF ALUMINUM CONDUCTORS, AS ALLOWED BY CODE, MAY BE SUBSTITUTED FOR COPPER. CONTRACTOR SHALL PROVIDE WRITTEN SUBSTITUTION REQUEST DEMONSTRATING THE THAT THE PROPOSED PRODUCT IS EQUIVALENT TO COPPER IN ALL ASPECTS.

MECHANICAL EQUIPMENT SCHEDULE								
NO.	EQUIPMENT NAME	HP/KW	VOLTS	PH	AMPS	CONDUIT	WIRE	CIRCUIT
EH-1	ELECTRIC WALL HEATER NO.1	1.5 KW	120	1		1/2"	#12	SEE UNIT PLANS
EH-2	ELECTRIC WALL HEATER NO.2	1.0KW	208	1		1/2"	#12	SEE FLOOR PLANS
EH-3	ELECTRIC WALL HEATER NO.3	1.0 KW	208	1		1/2"	#12	
EH-4	ELECTRIC WALL HEATER NO.4	500W	120	1		1/2"	#12	SEE E3.01
ERV-1	ERV FAN NO.1 (1BATH)	46W	120	1		1/2"	#12	SEE UNIT PLANS
ERV-2	ERV FAN NO.2 (2 BATH)	103W	120	1		1/2"	#12	SEE UNIT PLANS
ERV-3	ERV FAN NO.3 (1 BATH)	46W	120	1		1/2"	#12	SEE UNIT PLANS
GEF-1	GARAGE EXHAUST NO.1	1.5HP	208	3		1/2"	#12	H2-2,4
IAC-1	MINI SPLIT SYST NO.1 (INDOOR)							
OAC-1	MINI SPLIT SYST NO.1 (OUTDOOR)		208	1	28.0 MCA	1/2"	#10	H1-25,27
IHP-1	MINI SPLIT SYST NO.1 (INDOOR)							
OHP-1	MINI SPLIT SYST NO.1 (OUTDOOR)		208	1	25.0 MCA	3/4"	#8	H1-32,34 (TEMP)
IHP-2	MINI SPLIT SYST NO.2 (INDOOR)							
OHP-2	MINI SPLIT SYST NO.2 (OUTDOOR)		208	1	19.0 MCA	3/4"	#10	H1-36,38 (TEMP)
IHP-3	MINI SPLIT SYST NO.3 (INDOOR)							
OHP-3	MINI SPLIT SYST NO.3 (OUTDOOR)		208	1	25.0 MCA	3/4"	#8	H1-40,42 (TEMP)
IHP-4	MINI SPLIT SYST NO.4 (INDOOR)							
OHP-4	MINI SPLIT SYST NO.4 (OUTDOOR)		208	1	10.0 MCA	1/2"	#12	H2-1,3
RTU-1	AIR HANDLING UNIT NO.1		208	1	52.0 MCA	1"	#4	H2-15,17
SP-1	SUMP PUMP NO.1	1/2HP	120	1		1/2"	#12	H1-19
WH-1	WATER HEATER NO.1	4.5KW	208	1		1/2"	#12	SEE UNIT PLANS
WH-2	WATER HEATER NO.2	3.0KW	208	1		1/2"	#12	H2-22,24


GENERAL EQUIPMENT NOTES:

- CONTRACTOR/DESIGNER SHALL VERIFY ALL MECHANICAL EQUIPMENT CONNECTION LOAD REQUIREMENTS WITH THE MECHANICAL EQUIPMENT PROVIDER PRIOR TO ROUGH IN.
- MECHANICAL EQUIPMENT SIZES SHOWN IN THE MECHANICAL SCHEDULE ABOVE ARE FOR REFERENCE ONLY AND MAY NOT REFLECT THE ACTUAL EQUIPMENT TO BE INSTALLED.

M Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PH: (503) 234-0548
FAX: (503) 234-0677
INC. WWW.MFIA-ENG.COM
CONTACT: DENISE TAYLOR

STUDIO
3
ARCHITECTURE
INCORPORATED

275 COURT ST. NE
SALEM, OR 97301-3442
P: 503.390.6500
www.studio3architecture.com



PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E1.11

FLEX STATION RESIDENTIAL LOAD SUMMARY 'MC1'																	
UNIT TYPE:	QTY PER FLOOR				TOTAL	AREA (SF)	LTG/RECEPT (3VA / SF)	SM APPL (1500VA X2)	LAUNDRY (1500VA)	COOKING (CONNECTED)	MICROWAVE (CONNECTED)	DISHWASHER (CONNECTED)	ELECT DRYER (CONNECTED)	WATER HEATER (CONNECTED)	DISPOSAL (CONNECTED)	MOTORS (CONNECTED)	LARGEST OF: AC/HEATING (CONNECTED)
	Lv 1	Lv 2	Lv 3	Lv 4													
jio	---	4	4	4	12	430	1290	3000	1500	11500	1500	1200	3500	4500	900	0	3000
d/1bath	---	4	4	4	12	630	1890	3000	1500	11500	1500	1200	3500	4500	900	0	4500
d/2bath	---	5	5	5	15	930	2790	3000	1500	11500	1500	1200	3500	4500	900	0	6000
ALS:	0	13	13	13	39	26670	80010	117000	58500	448500	58500	46800	136500	175500	35100	0	180000

VOLTS: 208 3ph
TOTAL CONNECTED: 1336 KVA
DEMAND FACTOR: 0.29 Based on Total Number of Residential Units = 46 - 50 (See N.E.C. Article: 220.84)
TOTAL CALCULATED: 388 KVA
CALCULATED AMPS: 1076 AMPS

NOTE:

MFIA PANEL SCHEDULE																	
panel Panel H1		mounting SURFACE			location ELECT. RM			connected load amps		221		calculated load amps		231		231	
voltage 120/208V		phase 3		400A		bus & main		MLO									
C	service	va	a/p	no.	a b c	no.	a/p	va	service	C							
1	LIGHTS - PARKING LOT	1500	20/1	1	*	2	20/1	1500	RECEPT - FLR 1 / EF-2	2							
1	LIGHTS - BLDG EXTERIOR SIGNS	1500	20/1	3	*	4	20/1	500	RECEPT - ELEV MACH RM	2							
1	LIGHTS - PARKING GARAGE	1500	20/1	5	*	6	20/1	500	ENTRY ACCESS	5							
1	LIGHTS STAIR #1	1500	20/1	7	*	8	20/1	500	PHONE BOARD	5							
1	LIGHTS - STAIR #2	1500	20/1	9	*	10	20/1	500	COMM BOARD	5							
1	LTS & RECEPT - ELEV PIT/SHAFT	1500	20/1	11	*	12	20/1	1000	AUTO DOOR	6							
1	LIGHTS - FLR 1 & 2	1500	20/1	13	*	14	20/1	1000	AUTO DOOR	6							
1	LIGHTS - FLR 1 & 2 EGRESS	1500	20/1	15	*	16	20/1	1500	RECEPT - FLR 2 / EF-1	2							
1	LIGHTS - FLR 1 & 2	1500	20/1	17	*	18	20/1	500	SMOKE DAMPERS	5							
6	SP-1 SUMP PUMP	1176	20/1	19	*	20	20/1	500	LIGHTING CONTROL LCP	5							
3	EH-2 (STAIR #1)	1000	20/1	21	*	22	20/1	500	ELEV CAB LIGHTS	2							
3	EH-2 (STAIR #2)	1000	20/1	23	*	24	20/1	1500	ELEV CONTROL MODULE	5							
3	IAC/OAC-1	2900	30/2	25	*	26	20/1	500	FACP	5							
3	*	2900	*	27	*	28	20/1	0	SPARE								
2	RECEPT - TEMPORARY	1080	20/1	29	*	30	20/1	0	SPARE								
2	RECEPT - TEMPORARY	1080	20/1	31	*	32	35/2	2600	HP/OHP-1 (TEMP)	3							
2	RECEPT - TEMPORARY	1080	20/1	33	*	34	*	2600	*	3							
1	LIGHTS - TEMPORARY	1500	20/1	35	*	36	30/2	1976	HP/OHP-2 (TEMP)	3							
7	PANEL H2	9880	100/3	37	*	38	*	1976	*	3							
7	*	9680	*	39	*	40	35/2	2600	HP/OHP-3 (TEMP)	3							
7	*	7800	*	41	*	42	*	2600	*	3							
Phase A		28112 VA		NOTES:				line-line voltage		208							
Phase B		27360 VA															
Phase C		23956 VA										largest motor (va)					
Total Connected		79428 VA										0					
load code:		ph. A		ph. B		ph. C		total		factor		calculated load (va)					
1. LIGHTS=		4500		4500		6000 VA		15000		1.25		18750					
2. RECEPT.=		2580		3580		1080 VA		7240		1 + 0.5		7240					
3. HEATING=		7476		9100		5576 VA		22152		1.00		22152					
4. KITCHEN=		0		0		0 VA		0		1.00		0					
5. EQUIP.=		1500		500		2500 VA		4500		1.00		4500					
6. MOTORS=		2176		0		1000 VA		3176		*		3176					
7. MIS=		9880		9680		7800 VA		27360		1.00		27360					
(* 125% of the largest motor + 100% of the balance)										TOTAL =		83178					

MFIA PANEL SCHEDULE																			
panel Panel H2		mounting SURFACE				location ELECT RM				connected load amps				76					
voltage 120/208V		phase 3		100A		MLO		va		calculated load amps				78					
C	service	va	a/p	no.	a b c	no.	a/p	va	service	C									
3	IHP/OHP-4	1040	20/1	1	*	2	20/2	1040	GEF-1	6									
3	*	1040	20/1	3	*	4	*	1040	*										
	SPARE	0	20/1	5	*	6	20/1	200	RECEPT - TERRACE	2									
1	LIGHTS - FLR 3 & 4	1500	20/1	7	*	8	20/1	200	LIGHTS - TERRACE	1									
1	LIGHTS - FLR 3 & 4 (EGRESS)	1500	20/1	9	*	10	20/1	500	GAS GRILLS, FIRE TABLE	5									
2	RECEPT - FLR 3 / EF-1	1500	20/1	11	*	12	20/1	500	GAS SHUT-OFF	5									
2	RECEPT - FLR 4 / EF-1	1500	20/1	13	*	14	20/1	500	SMOKE DAMPERS	5									
6	RTU - 1	5400	60/2	15	*	16	20/1	500	EF-3	6									
6	*	5400	*	17	*	18	20/1	500	EF-4	6									
	SPARE	0	20/1	19	*	20	20/1	500	EH-4 (RISER RM)	3									
5	WATER VAULT (OPTIONAL)	20/1	21	*	22	30/2	1500	WH-2		3									
5	IRRIGATION (OPTIONAL)	20/1	23	*	24	*	1500	*		3									
	BLANK			25	*	26			BLANK										
	BLANK			27	*	28			BLANK										
	BLANK			29	*	30			BLANK										
	BLANK			31	*	32			BLANK										
	BLANK			33	*	34			BLANK										
	BLANK			35	*	36			BLANK										
	BLANK			37	*	38			BLANK										
	BLANK			39	*	40			BLANK										
	BLANK			41	*	42			BLANK										
Phase A		6280 VA				NOTES:				line-line voltage				208					
Phase B		11480 VA																	
Phase C		9600 VA								largest motor (va)									
Total Connected		27360 VA												0					
load code:		ph. A	ph. B		ph. C		total		factor	calculated load (va)									
1. LIGHTS=		1700	1500		0		VA	3200	1.25	4000									
2. RECEPT.=		1500	0		1700		VA	3200	1 + 0.5	3200									
3. HEATING=		1540	2540		1500		VA	5580	1.00	5580									
4. KITCHEN=		0	0		0		VA	0	1.00	0									
5. EQUIP.=		500	500		500		VA	1500	1.00	1500									
6. MOTORS=		1040	6940		5900		VA	13880	*	13880									
7. MISC=		0	0		0		VA	0	1.00	0									
(* 125% of the largest motor + 100% of the balance)									TOTAL=									28160	


LIGHTING FIXTURE LIST					
TYPE	LAMP	MANUFACTURER	CATALOG NUMBER	DESCRIPTION	OPTIONS
A1 A1E	LED 3000K 2000LM/80CRI 25W	LITHONIA (OR APPROVED OTHER)	ZLIN SERIES	TYPE :4" GEN. PURPOSE STRIP MOUNTING :SURFACE HOUSING :STEEL LENS/REFL :DIFFUSED ACRYLIC VOLTAGE :MVOLT BALLAST :LED DRIVER	TYPE 'AE' SIMILAR TO TYPE 'A' EXCEPT WITH EMERGENCY BATTERY BACK-UP EQUIP. RMS, TRASH RM, LEASE SPACE
A2 A2E	LED 3500K 3000LM/80CRI 23W	LITHONIA (OR APPROVED OTHER)	FEM148 SERIES	TYPE :4" ENCLOSED INDUSTRIAL MOUNTING :SURFACE HOUSING :POLYCARBONATE LENS/REFL :CLEAR POLYCARBONATE VOLTAGE :MVOLT BALLAST :LED DRIVER	WALL MOUNT AT +7'-0" AFF IN ROOF TERRACE MECH. ROOM. ELEVATOR PIT & TOP OF SHAFT
B1 B1E	LED 3000K 2152LM/80CRI 18.7W	LITHONIA (OR APPROVED OTHER)	WL4 20LP835 SERIES	TYPE :4" WRAP AROUND MOUNTING :SURFACE HOUSING :STEEL LENS/REFL :ACRYLIC VOLTAGE :MVOLT BALLAST :LED DRIVER	PROVIDE WITH INTEGRAL OCCUPANCY SENSOR, DIM50 STANDBY MODE STAIRWELLS
C1 C1E	LED 3000K 1275LM 12W	USAI LIGHTING (OR APPROVED OTHER)	BEVELED B4RD-G1 SERIES	TYPE :4.5" DIA. DOWNLIGHT MOUNTING :RECESSED HOUSING :ALUMINUM LENS/REFL :SOLITE/90 DEGREE BEAM VOLTAGE :MVOLT BALLAST :LED DRIVER (DIMMING)	C1E TO BE PROVIDED W/ EMERGENCY BATTERY BACK-UP TRIM FINISH PER ARCHITECT IC RATED LOBBIES, CORRIDORS, COMMUNITY RM
C2	LED 900LM/80CRI 3000K 10W	USAI LIGHTING (OR APPROVED OTHER)	B4RA SERIES	TYPE :4" DIA. ADJ. WALL WASHER MOUNTING :RECESSED HOUSING :ALUMINUM LENS/REFL :ACRYLIC VOLTAGE :MVOLT BALLAST :LED DRIVER (DIMMING)	TRIM PER ARCHITECT IC RATED 40 DEGREE BEAM/FIELD AIMED LOBBY, COMMUNITY RM
D1	(8) JCD/G9 LED 3000K/80CRI 24W	TBD (OR APPROVED OTHER)	TBD	TYPE :LARGE PENDANT MOUNTING :SUSPENDED HOUSING : LENS/REFL : VOLTAGE :120V BALLAST :LED DRIVER (0/10 DIMMING)	FINISH PER INTERIOR DECORATOR MOUNTING HEIGHT PER ARCH. LOBBY
S1	LED 3000K 975LM 14W	USAI LIGHTING (OR APPROVED OTHER)	BEVELED 1020 SERIES	TYPE :4.5" DIA. DOWNLIGHT MOUNTING :RECESSED HOUSING :ALUMINUM LENS/REFL :SOLITE VOLTAGE :MVOLT BALLAST :LED DRIVER	UL LISTED WET LOCATION FINISH PER ARCHITECT BUILDING ENTRANCES
S2	LED 3000K 2450LM 22W	CARDCO LIGHTING (OR APPROVED OTHER)	PWS SERIES	TYPE :EXTERIOR WALL PACK MOUNTING :SURFACE (+8'-0") HOUSING :ALUMINUM LENS/REFL :ACRYLIC VOLTAGE :MVOLT BALLAST :LED DRIVER	TYPE III DISTRIBUTION BUILDING SERVICE ENTRANCES
S3	LED 3000K 4398LM (49W)	LITHONIA LIGHTING (OR APPROVED EQUAL)	DSX0-LED-P2 SERIES	TYPE :AREA LIGHT MOUNTING :POLE MOUNT (+18'-0") HOUSING :CAST ALUMINUM LENS/REFL :TYPE III DISTRIBUTION VOLTAGE :MVOLT BALLAST :LED DRIVER	FINISH PER ARCHITECT. PROVIDE WITH PHOTOCELL & MEANS TO REDUCE LIGHT LEVELS DURING PERIODS OF INACTIVITY. PROVIDE WITH HOUSE SIDE SHIELD. PARKING LOT
U1	LED 650 LM 3000K 10W	LIGHTOLIER (OR APPROVED OTHER)	SSR SERIES	TYPE :5" DIA. DOWNLIGHT MOUNTING :SURFACE (J-BOX) HOUSING :ALUMINUM LENS/REFL :ACRYLIC VOLTAGE :MVOLT BALLAST :LED DRIVER (DIMMING)	FINISH PER ARCHITECT. UNIT KITCHEN, HALL, BATHROOM
U2	LED 750 LUMEN 3000K (18W)	KUZCO LIGHTING (OR APPROVED OTHER)	FM3511 SERIES	TYPE :11" DIA. CEILING LIGHT MOUNTING :SURFACE HOUSING :STEEL LENS/REFL :GLASS VOLTAGE :120V BALLAST :LED DRIVER	FINISH PER ARCHITECT. UNIT LIVING (STUDIO), BEDROOM
U3	LED 2400LM 3000K 29W	KUZCO LIGHTING (OR APPROVED OTHER)	VL61224 SERIES	TYPE :24" VANITY LIGHT MOUNTING :SURFACE (+6" ABOVE MIRROR) HOUSING :STEEL LENS/REFL :ACRYLIC VOLTAGE :120V BALLAST :LED DRIVER	--- FINISH UNIT BATHROOM
U4	LED 3000K 200LM 5W	WAC LIGHTING (OR APPROVED OTHER)	HR-LED90 SERIES	TYPE :UNDER CABINET LIGHT MOUNTING :SURFACE HOUSING :ALUMINUM LENS/REFL :ACRYLIC VOLTAGE :24V BALLAST :LED DRIVER (ELV DIMMING)	FINISH PER ARCHITECT. UNIT KITCHEN
'X'	LED (GREEN LETTERS) (1.5W)	LITHONIA DMF LIGHTING (OR APPROVED OTHER)	LE EL N SERIES DLED500EM-G	TYPE :EXIT SIGN MOUNTING :UNIVERSAL HOUSING :DIE-CAST ALUMINUM LENS/REFL :SINGLE FACE/DUAL FACE VOLTAGE :MVOLT BALLAST :NICKLE CADMIUM BATTERY	
'X2'	LED (GREEN LETTERS) (3.5W)	LITHONIA (OR APPROVED OTHER)	WLTE EL SERIES BLACK FINISH	TYPE :EXIT SIGN MOUNTING :UNIVERSAL HOUSING :DIE-CAST ALUMINUM LENS/REFL :SINGLE FACE VOLTAGE :MVOLT BALLAST :NICKLE CADMIUM BATTERY	UL LISTED WET LOCATION

GENERAL NOTES:


- A. ALL LIGHT FIXTURES SHALL HAVE ENERGY EFFICIENT LAMPING AND BALLASTS.
- B. LIGHT FIXTURES FOR LIVING UNITS SHALL BE "ENERGY STAR" RATED.
- C. EXTERIOR LIGHT FIXTURES SHALL BE "NIGHT SKY" FRIENDLY.
- D. VERIFY ALL FIXTURE FINISHES WITH ARCHITECT PRIOR TO BID.
- E. VERIFY ALL FIXTURE MOUNTING HEIGHTS WITH ARCHITECT PRIOR TO BID.
- F. VERIFY ALL FIXTURE LOCATIONS WITH ARCHITECT PRIOR TO ROUGH IN.
- G. ALL INTERIOR LIGHTING SHALL BE 3000 KELVIN UNLESS OTHERWISE NOTED.
- H. ALL PRODUCT SUBSTITUTIONS AND VALUE ENGINEERING SHALL BE SUBMITTED DURING BID PHASE, SHALL MEET DESIGN INTENT AND IS SUBJECT TO OWNER APPROVAL.
- I. CONTRACTOR SHALL CONSULT MANUFACTURER INSTALLATION INSTRUCTIONS FOR ALL FIXTURES AND DEVICES AND INSTALL AS INSTRUCTED. THIS INCLUDES ALL ELECTRICAL COMPONENTS REQUIRED FOR COMPLETE INSTALLATION. WORK SHALL BE PERFORMED SUCH THAT MANUFACTURER WARRANTY IS NOT VOIDED.
- J. IF NECESSARY, CONTRACTOR SHALL PROVIDE IC RATED BOXES FOR ANY APPROVED, SUBSTITUTED FIXTURES NOT MEETING INSULATED CEILING REQUIREMENTS.
- K. BUILDING MOUNTED EXTERIOR WALL SCONCES, TYPE S3b, TO BE CONTROLLED VIA PHOTOCELL AND BE PROVIDED WITH A TIME CLOCK TO REDUCE LIGHT OUTPUT BY 30% DURING LATE NIGHT TO REDUCE REFLECTANCE INTO TENANT LIVING UNITS. FIXTURES DESIGNATED TO BE EGRESS SHALL BE BE WIRED SUCH THAT IN THE EVENT OF A POWER OUTAGE, THE LIGHTS AUTOMATICALLY RETURN TO FULL OUTPUT. TIME CLOCK SETTINGS TO BE DETERMINED BY THE OWNER.

KEYED LIGHTING NOTES:


1. STAIRWELL LIGHT FIXTURES TO BE EQUIPPED WITH FACTORY INSTALLED (OR REMOTE) OCCUPANCY SENSORS FOR MIN. 50% LIGHT REDUCTION DURING PERIODS OF NO ACTIVITY.



3 POLE BASE MOUNTING DETAIL
NO SCALE




1 BATHROOM SWITCHING DIAGRAM - TYPICAL
NO SCALE




2 LIGHTING CONTROL SYSTEM DIAGRAM - LCP
NO SCALE

TYPICAL FOR EACH BUILDING



4 EMERGENCY EGRESS LIGHTING - UNSWITCHED
NO SCALE



4 EMERGENCY EGRESS LIGHTING - SWITCHED
NO SCALE

STUDIO

3
ARCHITECTURE
INCORPORATED

275 COURT ST. NE
SALEM, OR 97301-3442
P: 503.390.6500
www.studio3architecture.com



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E1.21

M
E
I
A
Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0677
WWW.MEIA-ENG.COM
CONTACT: DENISE TAYLOR




Figure 308.2.1
Unobstructed Forward Reach




Figure 308.3.1
Unobstructed Side Reach




Figure 308.2.2
Obstructed High Forward Reach




Figure 308.3.2
Obstructed High Side Reach

1 ADA REACH REQUIREMENTS

308.2 Forward Reach.

308.2.1 Unobstructed. Where a forward reach is unobstructed, the high forward reach shall be 48" maximum and the low forward reach shall be 15" minimum above the floor or ground.





308.2.2 Obstructed High Reach. Where a high forward reach is over an obstruction, the clear floor or ground space shall extend beneath the element for a distance not less than the required reach depth over the obstruction. The high forward reach shall be 48" maximum where the reach depth is 20" maximum. Where the reach depth exceeds 20", the high forward reach shall be 44" maximum and the reach depth shall be 25" maximum.

308.3 Side Reach.

308.3.1 Unobstructed. Where a clear floor or ground space allows a parallel approach to an element and the side reach is unobstructed, the high side reach shall be 48" maximum and the low side reach shall be 15" minimum above the floor or ground.

Exception: Existing elements shall be permitted at 54" maximum above the floor or ground.

308.3.2 Obstructed High Reach. Where a clear floor or ground space allows a parallel approach to an object and the high side reach is over an obstruction, the height of the obstruction shall be 34" maximum and the depth of the obstruction shall be 24" maximum. The high side reach shall be 48" maximum for a reach depth of 10" maximum. Where the reach depth exceeds 10", the high side reach shall be 46" maximum for a reach depth of 24" maximum.




NOTES:

1. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE PLUMBING CONTRACTOR PRIOR TO ROUGH IN, TO ENSURE THAT ELECTRICAL DEVICES ARE NOT INSTALLED WHERE THEY WILL CREATE CONFLICT.
2. PREFERRED INSTALLATION SHALL HAVE THE ELECTRICAL DEVICES ON A WALL OPPOSITE THE WORK OF ANY OTHER TRADE.
3. COORDINATE WITH WATER METER INSTALLER FOR EXACT LOCATION OF DUPLEX RECEPTACLE, WHERE REQUIRED.
4. FIELD COORDINATE WITH ALL TRADES PRIOR TO ROUGH IN.

2 SWITCHBOARD/PANEL LABELING DETAIL

NOTE: ALL LETTERS ARE ENGRAVED WHITE




3 SMOKE/FIRE DAMPER CONTROL DIAGRAM

ADDRESSABLE DETECTOR CONTROL

- A RELAY TO BE 'NORMALLY OPEN'. TDOD (TIME DELAY ON DE-ENERGY) SET FOR 15 SECONDS. RELAY TO CLOSE UPON SIGNAL FROM HVAC CONTROL SYSTEM (ALLOWS DAMPER TO OPEN); DAMPERS TO CLOSE ON DE-ENERGIZE AFTER 15 SEC. TIME-OUT. PROVIDE WITH 20A CONTACTS AND COIL VOLTAGE AS REQ'D BY HVAC CONTROL SYSTEM. MOUNT RELAY IN NEMA 1 ENCLOSURE ADJACENT TO HVAC CONTROL PANEL.
- B RELAY TO BE 'NORMALLY ENERGIZED'. RELAY TO BE DE-ENERGIZED UPON SIGNAL FROM FIRE ALARM SYSTEM (ALLOWS DAMPERS TO CLOSE). PROGRAM FIRE ALARM SYSTEM FOR 15 SECOND DELAY BETWEEN SMOKE DETECTOR ACTIVATION AND FIRE/SMOKE DAMPER SHUTDOWN. PROVIDE WITH 20A CONTACTS AND COIL VOLTAGE AS REQ'D BY FIRE ALARM SYSTEM. MOUNT RELAY IN NEMA 1 ENCLOSURE ADJACENT TO FIRE/SMOKE DAMPER.

4 TYPICAL WASHER/DRYER ALCOVE



5 GAS APPLIANCE EMERGENCY SHUT-OFF DIAGRAM




EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED
BETWEEN THE ORIGINAL SIGNED AND SEALED
DOCUMENTS PREPARED BY THE ARCHITECTS
AND/OR THEIR CONSULTANTS, AND ANY COPY OF
THE DOCUMENTS TRANSMITTED BY MAIL, FAX,
ELECTRONICALLY OR OTHERWISE, THE ORIGINAL
SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA



1 FIRST FLOOR LIGHTING PLAN
E2.01 SCALE: 1/8" = 1'-0"

GENERAL LIGHTING NOTES:

- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL AND MAY NOT ACCURATELY REFLECT ACTUAL CONSTRUCTION CONDITIONS. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL ELECTRICAL EQUIPMENT, WITH ALL TRADES PRIOR TO AND DURING CONSTRUCTION.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR ALL LOCATIONS, MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES PRIOR TO THE START OF ANY WORK.
- REFER TO SHEET E1.21 FOR LIGHT FIXTURE SCHEDULE.
- OCCUPANCY SENSORS SHALL BE FIELD ADJUSTED TO ENSURE COVERAGE AND PROPER CONTROL.
- PROVIDE DIGITAL LIGHTING CONTROLS FOR EACH ROOM/SPACE, CONSISTING OF MULTI-BUTTON SWITCH(ES), OCC SENSORS, POWER PACKS, DAYLIGHT SENSORS, DIMMERS, INTERCONNECTING WIRING, ETC.
- CORRIDOR LIGHTING TO BE CONSTANT "ON" AND PROVIDED WITH LOCAL MANUAL OVERRIDE SWITCHES FOR MAINTENANCE. REFER TO SHEET E1.22 FOR SWITCH WIRING DIAGRAMS.
- REFER TO SHEET E1.23 FOR LIGHTING CONTROL DIAGRAMS AND DESIGN INTENT. VERIFY LIGHTING CONTROLLABILITY WITH ARCHITECT AND/OR OWNER'S REPRESENTATIVE TO DETERMINE EXACT NEEDS FOR ALL PUBLIC/Common AREAS SUCH AS LOBBIES, OFFICES, LOUNGE AREAS, ETC., PRIOR TO THE START OF ANY WORK.
- THERE SHALL BE NO SURFACE MOUNTED FIXTURES OR PATHWAYS (CONDUIT, ETC.) IN ANY PUBLICLY ACCESSIBLE SPACES, INCLUDING STAIRWELLS AND EXIT PASSAGEWAYS WITHOUT PRIOR APPROVAL BY OWNER AND ARCHITECT. ROUTE ALL PATHWAYS WITHIN STUD CAVITIES OR ABOVE FINISHED CEILINGS.
- ALL EGRESS FIXTURES SHALL BE WIRED SUCH THAT IN THE EVENT OF A POWER FAILURE, ALL LIGHTS WILL AUTOMATICALLY RETURN TO FULL POWER. REFER TO SWITCHING DETAILS ON SHEET E1.22.


KEYED NOTES:

- CONTINUE CIRCUIT UP THROUGH THE STAIRWELL.
- LEASE SPACE LIGHTING TO BE CONTROLLED VIA OCCUPANCY SENSOR(S). INTENT IS THAT THE NIGHT LIGHTS (N.L.) ARE TO BE "ON" 24/7 AND ONLY ILLUMINATED AT NIGHT VIA PHOTOCELL FOR DUSK-TILL-DAWN OPERATION. NIGHT LIGHT FIXTURES SHALL ALSO BE EQUIPPED WITH EMERGENCY BATTERY BACKUP IN THE EVENT OF A POWER FAILURE. ALL LIGHT FIXTURES IN THE LEASE SPACE ARE TO BE ON A SINGLE CIRCUIT AND TEMPORARILY FED FROM THE HOUSE PANEL.
- TIE INTO TEMPORARY LIGHTING CIRCUIT AND ENSURE BATTERY BACK UP POWER FOR EGRESS.
- LIGHT FIXTURES IN THIS SPACE CONTROLLED BY CEILING MOUNT OCCUPANCY SENSOR.
- CORRIDOR LIGHT FIXTURES IN THIS SPACE CIRCUITED VIA LIGHTING CONTROL PANEL TO DIM LIGHTING BY 50% DURING LOW ACTIVITY PERIODS (EX: 12AM TO 5AM). CEILING MOUNT OCCUPANCY SENSORS SHALL RESTORE LIGHTING TO FULL OUTPUT UPON DETECTION OF OCCUPANCY AND REDUCE NO LESS THAN 15 MINUTES OF VACANCY.
- CORRIDOR LIGHT FIXTURES DESIGNATED AS EGRESS SHALL REMAIN ON 24/7.

M F I A
INC. Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR

SHEET:

E2.01



GENERAL LIGHTING NOTES:

- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL AND MAY NOT ACCURATELY REFLECT ACTUAL CONSTRUCTION CONDITIONS. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL ELECTRICAL EQUIPMENT, WITH ALL TRADES PRIOR TO AND DURING CONSTRUCTION.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR ALL LOCATIONS, MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES PRIOR TO THE START OF ANY WORK.
- REFER TO SHEET E1.21 FOR LIGHT FIXTURE SCHEDULE.
- OCCUPANCY SENSORS SHALL BE FIELD ADJUSTED TO ENSURE COVERAGE AND PROPER CONTROL.
- PROVIDE DIGITAL LIGHTING CONTROLS FOR EACH ROOM/SPACE, CONSISTING OF MULTI-BUTTON SWITCH(ES), OCC SENSORS, POWER PACKS, DAYLIGHT SENSORS, DIMMERS, INTERCONNECTING WIRING, ETC.
- CORRIDOR LIGHTING TO BE CONSTANT "ON" AND PROVIDED WITH LOCAL MANUAL OVERRIDE SWITCHES FOR MAINTENANCE. REFER TO SHEET E1.22 FOR SWITCH WIRING DIAGRAMS.
- REFER TO SHEET E1.23 FOR LIGHTING CONTROL DIAGRAMS AND DESIGN INTENT. VERIFY LIGHTING CONTROLLABILITY WITH ARCHITECT AND/OR OWNER'S REPRESENTATIVE TO DETERMINE EXACT NEEDS FOR ALL PUBLIC/COMMON AREAS SUCH AS LOBBIES, OFFICES, LOUNGE AREAS, ETC., PRIOR TO THE START OF ANY WORK.
- THERE SHALL BE NO SURFACE MOUNTED FIXTURES OR PATHWAYS (CONDUIT, ETC.) IN ANY PUBLICLY ACCESSIBLE SPACES, INCLUDING STAIRWELLS AND EXIT PASSAGEWAYS WITHOUT PRIOR APPROVAL BY OWNER AND ARCHITECT. ROUTE ALL PATHWAYS WITHIN STUD CAVITIES OR ABOVE FINISHED CEILINGS.
- ALL EGRESS FIXTURES SHALL BE WIRED SUCH THAT IN THE EVENT OF A POWER FAILURE, ALL LIGHTS WILL AUTOMATICALLY RETURN TO FULL POWER. REFER TO SWITCHING DETAILS ON SHEET E1.22.

KEYED NOTES:

- CONTINUE CIRCUIT UP THROUGH THE STAIRWELL.
- LEASE SPACE LIGHTING TO BE CONTROLLED VIA OCCUPANCY SENSOR(S). INTENT IS THAT THE NIGHT LIGHTS (N.L.) ARE TO BE "ON" 24/7 AND ONLY ILLUMINATED AT NIGHT VIA PHOTOCELL FOR DUSK-TILL-DAWN OPERATION. NIGHT LIGHT FIXTURES SHALL ALSO BE EQUIPPED WITH EMERGENCY BATTERY BACKUP IN THE EVENT OF A POWER FAILURE. ALL LIGHT FIXTURES IN THE LEASE SPACE ARE TO BE ON A SINGLE CIRCUIT AND TEMPORARILY FED FROM THE HOUSE PANEL.
- TIE INTO TEMPORARY LIGHTING CIRCUIT AND ENSURE BATTERY BACK UP POWER FOR EGRESS.
- LIGHT FIXTURES IN THIS SPACE CONTROLLED BY CEILING MOUNT OCCUPANCY SENSOR.
- CORRIDOR LIGHT FIXTURES IN THIS SPACE CIRCUITED VIA LIGHTING CONTROL PANEL TO DIM LIGHTING BY 50% DURING LOW ACTIVITY PERIODS (EX: 12AM TO 5AM). CEILING MOUNT OCCUPANCY SENSORS SHALL RESTORE LIGHTING TO FULL OUTPUT UPON DETECTION OF OCCUPANCY AND REDUCE NO LESS THAN 15 MINUTES OF VACANCY.
- CORRIDOR LIGHT FIXTURES DESIGNATED AS EGRESS SHALL REMAIN ON 24/7.

STUDIO

3

ARCHITECTURE
INCORPORATED

275 COURT ST. NE
SALEM, OR 97301-3442
P: 503.390.6500
www.studio3architecture.com



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022


REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E2.02

M F I A
INC. Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR



1 THIRD FLOOR LIGHTING PLAN
E2.03 SCALE: 1/8" = 1'-0"

GENERAL LIGHTING NOTES:

- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL AND MAY NOT ACCURATELY REFLECT ACTUAL CONSTRUCTION CONDITIONS. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL ELECTRICAL EQUIPMENT, WITH ALL TRADES PRIOR TO AND DURING CONSTRUCTION.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR ALL LOCATIONS, MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES PRIOR TO THE START OF ANY WORK.
- REFER TO SHEET E1.21 FOR LIGHT FIXTURE SCHEDULE.
- OCCUPANCY SENSORS SHALL BE FIELD ADJUSTED TO ENSURE COVERAGE AND PROPER CONTROL.
- PROVIDE DIGITAL LIGHTING CONTROLS FOR EACH ROOM/SPACE, CONSISTING OF MULTI-BUTTON SWITCH(ES), OCC SENSORS, POWER PACKS, DAYLIGHT SENSORS, DIMMERS, INTERCONNECTING WIRING, ETC.
- CORRIDOR LIGHTING TO BE CONSTANT "ON" AND PROVIDED WITH LOCAL MANUAL OVERRIDE SWITCHES FOR MAINTENANCE. REFER TO SHEET E1.22 FOR SWITCH WIRING DIAGRAMS.
- REFER TO SHEET E1.23 FOR LIGHTING CONTROL DIAGRAMS AND DESIGN INTENT. VERIFY LIGHTING CONTROLLABILITY WITH ARCHITECT AND/OR OWNER'S REPRESENTATIVE TO DETERMINE EXACT NEEDS FOR ALL PUBLIC/Common AREAS SUCH AS LOBBIES, OFFICES, LOUNGE AREAS, ETC., PRIOR TO THE START OF ANY WORK.
- THERE SHALL BE NO SURFACE MOUNTED FIXTURES OR PATHWAYS (CONDUIT, ETC.) IN ANY PUBLICLY ACCESSIBLE SPACES, INCLUDING STAIRWELLS AND EXIT PASSAGEWAYS WITHOUT PRIOR APPROVAL BY OWNER AND ARCHITECT. ROUTE ALL PATHWAYS WITHIN STUD CAVITIES OR ABOVE FINISHED CEILINGS.
- ALL EGRESS FIXTURES SHALL BE WIRED SUCH THAT IN THE EVENT OF A POWER FAILURE, ALL LIGHTS WILL AUTOMATICALLY RETURN TO FULL POWER. REFER TO SWITCHING DETAILS ON SHEET E1.22.

KEYED NOTES:

- CONTINUE CIRCUIT UP THROUGH THE STAIRWELL.
- LEASE SPACE LIGHTING TO BE CONTROLLED VIA OCCUPANCY SENSOR(S). INTENT IS THAT THE NIGHT LIGHTS (N.L.) ARE TO BE "ON" 24/7 AND ONLY ILLUMINATED AT NIGHT VIA PHOTOCELL FOR DUSK-TILL-DAWN OPERATION. NIGHT LIGHT FIXTURES SHALL ALSO BE EQUIPPED WITH EMERGENCY BATTERY BACKUP IN THE EVENT OF A POWER FAILURE. ALL LIGHT FIXTURES IN THE LEASE SPACE ARE TO BE ON A SINGLE CIRCUIT AND TEMPORARILY FED FROM THE HOUSE PANEL.
- TIE INTO TEMPORARY LIGHTING CIRCUIT AND ENSURE BATTERY BACK UP POWER FOR EGRESS.
- LIGHT FIXTURES IN THIS SPACE CONTROLLED BY CEILING MOUNT OCCUPANCY SENSOR.
- CORRIDOR LIGHT FIXTURES IN THIS SPACE CIRCUITED VIA LIGHTING CONTROL PANEL TO DIM LIGHTING BY 50% DURING LOW ACTIVITY PERIODS (EX: 12AM TO 5AM). CEILING MOUNT OCCUPANCY SENSORS SHALL RESTORE LIGHTING TO FULL OUTPUT UPON DETECTION OF OCCUPANCY AND REDUCE NO LESS THAN 15 MINUTES OF VACANCY.
- CORRIDOR LIGHT FIXTURES DESIGNATED AS EGRESS SHALL REMAIN ON 24/7.

STUDIO

3

ARCHITECTURE
INCORPORATED

275 COURT ST. NE
SALEM, OR 97301-3442
P: 503.390.6500
www.studio3architecture.com



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

M F I A
INC. Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR
WWW.MFIA-ENG.COM

SHEET:

E2.03



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED
BETWEEN THE ORIGINAL SIGNED AND SEALED
DOCUMENTS PREPARED BY THE ARCHITECTS
AND/OR THEIR CONSULTANTS, AND ANY COPY OF
THE DOCUMENTS TRANSMITTED BY MAIL, FAX,
ELECTRONICALLY OR OTHERWISE, THE ORIGINAL
SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022


REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

**M
F
I
A**
INC.

Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR

SHEET:

E2.04


1 FOURTH FLOOR LIGHTING PLAN
E2.04 SCALE: 1/8" = 1'-0"

GENERAL LIGHTING NOTES:

- ELECTRICAL DRAWINGS ARE DIAGRAMMATICAL AND MAY NOT ACCURATELY REFLECT ACTUAL CONSTRUCTION CONDITIONS. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE INSTALLATION OF ALL ELECTRICAL EQUIPMENT, WITH ALL TRADES PRIOR TO AND DURING CONSTRUCTION.
- THE ELECTRICAL CONTRACTOR SHALL REFER TO THE ARCHITECTURAL DRAWINGS FOR ALL LOCATIONS, MOUNTING HEIGHTS AND FINISHES OF DEVICES AND FIXTURES PRIOR TO THE START OF ANY WORK.
- REFER TO SHEET E1.21 FOR LIGHT FIXTURE SCHEDULE.
- OCCUPANCY SENSORS SHALL BE FIELD ADJUSTED TO ENSURE COVERAGE AND PROPER CONTROL.
- PROVIDE DIGITAL LIGHTING CONTROLS FOR EACH ROOM/SPACE, CONSISTING OF MULTI-BUTTON SWITCH(ES), OCC SENSORS, POWER PACKS, DAYLIGHT SENSORS, DIMMERS, INTERCONNECTING WIRING, ETC.
- CORRIDOR LIGHTING TO BE CONSTANT "ON" AND PROVIDED WITH LOCAL MANUAL OVERRIDE SWITCHES FOR MAINTENANCE. REFER TO SHEET E1.22 FOR SWITCH WIRING DIAGRAMS.
- REFER TO SHEET E1.23 FOR LIGHTING CONTROL DIAGRAMS AND DESIGN INTENT. VERIFY LIGHTING CONTROLLABILITY WITH ARCHITECT AND/OR OWNER'S REPRESENTATIVE TO DETERMINE EXACT NEEDS FOR ALL PUBLIC/Common AREAS SUCH AS LOBBIES, OFFICES, LOUNGE AREAS, ETC., PRIOR TO THE START OF ANY WORK.
- THERE SHALL BE NO SURFACE MOUNTED FIXTURES OR PATHWAYS (CONDUIT, ETC.) IN ANY PUBLICLY ACCESSIBLE SPACES, INCLUDING STAIRWELLS AND EXIT PASSAGEWAYS WITHOUT PRIOR APPROVAL BY OWNER AND ARCHITECT. ROUTE ALL PATHWAYS WITHIN STUD CAVITIES OR ABOVE FINISHED CEILINGS.
- ALL EGRESS FIXTURES SHALL BE WIRED SUCH THAT IN THE EVENT OF A POWER FAILURE, ALL LIGHTS WILL AUTOMATICALLY RETURN TO FULL POWER. REFER TO SWITCHING DETAILS ON SHEET E1.22.

KEYED NOTES:

- CONTINUE CIRCUIT UP THROUGH THE STAIRWELL.
- LEASE SPACE LIGHTING TO BE CONTROLLED VIA OCCUPANCY SENSOR(S). INTENT IS THAT THE NIGHT LIGHTS (N.L.) ARE TO BE "ON" 24/7 AND ONLY ILLUMINATED AT NIGHT VIA PHOTOCELL FOR DUSK-TILL-DAWN OPERATION. NIGHT LIGHT FIXTURES SHALL ALSO BE EQUIPPED WITH EMERGENCY BATTERY BACKUP IN THE EVENT OF A POWER FAILURE. ALL LIGHT FIXTURES IN THE LEASE SPACE ARE TO BE ON A SINGLE CIRCUIT AND TEMPORARILY FED FROM THE HOUSE PANEL.
- TIE INTO TEMPORARY LIGHTING CIRCUIT AND ENSURE BATTERY BACK UP POWER FOR EGRESS.
- LIGHT FIXTURES IN THIS SPACE CONTROLLED BY CEILING MOUNT OCCUPANCY SENSOR.
- CORRIDOR LIGHT FIXTURES IN THIS SPACE CIRCUITED VIA LIGHTING CONTROL PANEL TO DIM LIGHTING BY 50% DURING LOW ACTIVITY PERIODS (EX: 12AM TO 5AM). CEILING MOUNT OCCUPANCY SENSORS SHALL RESTORE LIGHTING TO FULL OUTPUT UPON DETECTION OF OCCUPANCY AND REDUCE NO LESS THAN 15 MINUTES OF VACANCY.
- CORRIDOR LIGHT FIXTURES DESIGNATED AS EGRESS SHALL REMAIN ON 24/7.



1 SECOND FLOOR POWER PLAN
 E3.02 SCALE: 1/8" = 1'-0"

GENERAL POWER NOTES:

- A. ALL PLANS ARE CONSIDERED DIAGRAMMATICAL. THEREFORE ALL EQUIPMENT SIZES AND DEVICE LOCATIONS ARE APPROXIMATE AND SUBJECT TO FIELD CONDITIONS AND PRODUCT APPROVAL.
- B. ELECTRICAL EQUIPMENT SHOWN ON THE PLANS IS APPROXIMATE, BASED ON STANDARD PRODUCTS. CONTRACTOR SHALL VERIFY ANY SUBMITTED EQUIPMENT WILL FIT WITHIN THE SPACE PROVIDED, PRIOR TO PRODUCT SUBMITTAL REVIEW.
- C. GENERAL PURPOSE CONVENIENCE RECEPTACLES LOCATED ON THE BUILDING EXTERIOR, OTHER THAN INTERIOR COURT YARD, SHALL BE EQUIPPED WITH A LOCKING, WEATHER PROOF COVER.
- D. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO VERIFY EXACT LOCATIONS AND FINISHES FOR LIGHT FIXTURES AND DEVICES.
- E. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE CIVIL ENGINEER, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- F. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE MECHANICAL AND PLUMBING CONTRACTORS, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- G. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LANDSCAPING CONTRACTOR, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- H. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE ("T" SERIES) PLANS, INCLUDING FIRE ALARM AND SYSTEMS INSTALLER, AND PROVIDE ROUGH IN AS NEEDED.
- I. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING THE ELECTRICAL PLANS AND ALL OTHER SUPPORTING DOCUMENTS PRIOR TO THE START OF ANY WORK. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION UPON DISCOVERY.
- J. ALL LIGHTING, DEVICES AND HVAC EQUIPMENT LOCATED IN THE RETAIL TENANT SPACES IS CONSIDERED TEMPORARY AND SHALL BE REMOVED AND/OR DISCONNECTED FROM THE HOUSE POWER AT THE TIME OF THE TENANT'S SPACE IMPROVEMENT WORK.

KEYED NOTES:

1. VERIFY ELEVATOR EQUIPMENT LOCATION AND ELECTRICAL REQUIREMENTS WITH ARCHITECT AND/OR ELEVATOR PROVIDER.
2. PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR AUTOMATIC DOOR OPENERS.
3. LOW VOLTAGE/COMMUNICATIONS SYSTEM DEMARCATION BOARD(S). COORDINATE LOCATIONS AND ELECTRICAL POWER REQUIREMENTS WITH THE TELECOM AND LOW VOLTAGE SYSTEMS INSTALLER(S). PROVIDE ROUGH IN AND/OR FINAL ELECTRICAL POWER CONNECTIONS. REFER PANEL "H1" SCHEDULE ON E1.12 FOR RESERVED CIRCUITS.
4. PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR BUILDING ENTRY ACCESS CONTROL SYSTEM AND PROVIDE ROUGH IN AND WIRING TO ACCESS POINTS AS DETERMINED BY OWNER AND/OR ARCHITECT. CONSULT WITH THE SYSTEM INSTALLER FOR ADDITIONAL INFORMATION.
5. PROVIDE ONE 3" EMPTY CONDUIT W/PULL STRING FROM BUILDING SERVICE ENTRANCE TO EACH RETAIL SPACE, ROUTED OVERHEAD AND STUBBED INTO CEILING SPACE AND CAPPED AT BOTH ENDS FOR FUTURE TENANT'S SERVICE. SUCH SERVICE SHALL BE CONNECTED AS PART OF THE TENANT'S IMPROVEMENTS. CONSULT ARCHITECT AND/OR OWNER TO DETERMINE BEST LOCATION PRIOR TO ROUGH IN.
6. PROVIDE AND INSTALL OVERHEAD DOOR OPENER. FINAL CONNECTION SHALL BE MADE BY TENANT.
7. PROVIDE 120V TWIST TIMER SWITCH (MAX. 60 MINUTES, "NO HOLD") IN WEATHER PROOF BOX FOR GAS GRILL AND FIRE PIT IGNITER CONTROLS. CIRCUIT FROM PANEL H2.
8. PROVIDE EMERGENCY SHUTOFF CONTROLS FOR GAS APPLIANCES LOCATED ON TERRACE. COORDINATE INSTALLATION WITH MECHANICAL CONTRACTOR. SEE DETAIL 5/E1.22 FOR EMERGENCY SHUT-OFF DIAGRAM. CIRCUIT FROM PANEL H2.
9. REFER TO MECHANICAL PLANS FOR GRILL HOOD INFORMATION AND PROVIDE ELECTRICAL CONNECTIONS AS REQUIRED. SEE E3.05 FOR EXHAUST FAN LOCATION.

KEYED APARTMENT NOTES:

1. PROVIDE WIRE CONNECTION FOR THERMOSTAT(S). COORDINATE WITH MECHANICAL INSTALLER FOR EXACT LOCATION AND POWER REQUIREMENTS PRIOR TO ROUGH IN. THERMOSTATS TO BE MOUNTED AT 48" AFF MAX. TO HIGHEST OPERABLE PART.
2. PROVIDE ONE 20A, 120V, 1P GFCI DUPLEX RECEPTACLE UNDER KITCHEN SINK FOR DISPOSAL POWER CONNECTION. DISPOSAL TO BE PROVIDED WITH "SAFEAIRE" SINK DISPOSAL AIR SWITCH, MOUNTED PER ARCHITECT'S DIRECTION. VERIFY DEVICE FINISH WITH ARCHITECT PRIOR TO ORDERING.
3. PROVIDE ONE 15A SPLIT BUSS SWITCHED RECEPTACLE. REFER TO LIGHTING PLANS FOR SWITCH LOCATION.
4. PROVIDE ONE 15A, RECEPTACLE CIRCUIT FROM TENANT LOAD CENTER FOR TELECOM SMART PANEL. COORDINATE WORK WITH SERVICE PROVIDER FOR EXACT LOCATION AND FINAL CONNECTION.
5. FOR RANGE HOODS/MICROWAVES PROVIDED WITH A CORD & PLUG SET, PROVIDE A 20A DUPLEX RECEPTACLE LOCATED INSIDE THE OVERHEAD CABINET. HARDWIRED APPLIANCES MAY BE CIRCUITED VIA J-BOX MOUNTED FLUSH OR RECESSED INTO THE WALL DIRECTLY BEHIND THE APPLIANCE.
6. REFER TO SHEET E1.21 FOR TYPICAL BATHROOM SWITCHING DIAGRAM.
7. REFER TO SHEET E1.22 FOR TYPICAL LAUNDRY ALCOVE DETAIL.

APPLIANCE CIRCUITS

- | | |
|----------------------|--------------------------|
| 1. REFRIGERATOR LC-6 | 5. DISPOSAL LC-16 |
| 2. MICRO/HOOD LC-8 | 6. WASHER LC-13 |
| 3. RANGE LC-10,12 | 7. DRYER LC-15,17 |
| 4. DISHWASHER LC-14 | 8. SMART PNL LC-23 (OPT) |

MFA Consulting Engineers
 2007 S.E. Ash St.
 Portland, OR 97214
 PHN: (503) 234-0548
 FAX: (503) 234-0877
 CONTACT: DENISE TAYLOR

STUDIO

3
 ARCHITECTURE
 INCORPORATED

275 COURT ST. NE
 SALEM, OR 97301-3442
 P: 503.390.6500
 www.studio3architecture.com



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.


PROJECT # 2019-149
 DATE: 05/20/2022

REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
 1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E3.02



1 THIRD FLOOR POWER PLAN
E3.03 SCALE: 1/8" = 1'-0"

GENERAL POWER NOTES:

- A. ALL PLANS ARE CONSIDERED DIAGRAMMATICAL. THEREFORE ALL EQUIPMENT SIZES AND DEVICE LOCATIONS ARE APPROXIMATE AND SUBJECT TO FIELD CONDITIONS AND PRODUCT APPROVAL.
- B. ELECTRICAL EQUIPMENT SHOWN ON THE PLANS IS APPROXIMATE, BASED ON STANDARD PRODUCTS. CONTRACTOR SHALL VERIFY ANY SUBMITTED EQUIPMENT WILL FIT WITHIN THE SPACE PROVIDED, PRIOR TO PRODUCT SUBMITTAL REVIEW.
- C. GENERAL PURPOSE CONVENIENCE RECEPTACLES LOCATED ON THE BUILDING EXTERIOR, OTHER THAN INTERIOR COURT YARD, SHALL BE EQUIPPED WITH A LOCKING, WEATHER PROOF COVER.
- D. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO VERIFY EXACT LOCATIONS AND FINISHES FOR LIGHT FIXTURES AND DEVICES.
- E. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE CIVIL ENGINEER, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- F. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE MECHANICAL AND PLUMBING CONTRACTORS, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- G. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LANDSCAPING CONTRACTOR, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- H. ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE ('T' SERIES) PLANS, INCLUDING FIRE ALARM AND SYSTEMS INSTALLER, AND PROVIDE ROUGH IN AS NEEDED.
- I. ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING THE ELECTRICAL PLANS AND ALL OTHER SUPPORTING DOCUMENTS PRIOR TO THE START OF ANY WORK. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION UPON DISCOVERY.
- J. ALL LIGHTING, DEVICES AND HVAC EQUIPMENT LOCATED IN THE RETAIL TENANT SPACES IS CONSIDERED TEMPORARY AND SHALL BE REMOVED AND/OR DISCONNECTED FROM THE HOUSE POWER AT THE TIME OF THE TENANT'S SPACE IMPROVEMENT WORK.

KEYED NOTES:

- 1. VERIFY ELEVATOR EQUIPMENT LOCATION AND ELECTRICAL REQUIREMENTS WITH ARCHITECT AND/OR ELEVATOR PROVIDER.
- 2. PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR AUTOMATIC DOOR OPENERS.
- 3. LOW VOLTAGE/COMMUNICATIONS SYSTEM DEMARCATION BOARD(S). COORDINATE LOCATIONS AND ELECTRICAL POWER REQUIREMENTS WITH THE TELECOM AND LOW VOLTAGE SYSTEMS INSTALLER(S). PROVIDE ROUGH IN AND/OR FINAL ELECTRICAL POWER CONNECTIONS. REFER PANEL 'H1' SCHEDULE ON E1.12 FOR RESERVED CIRCUITS.
- 4. PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR BUILDING ENTRY ACCESS CONTROL SYSTEM AND PROVIDE ROUGH IN AND WIRING TO ACCESS POINTS AS DETERMINED BY OWNER AND/OR ARCHITECT. CONSULT WITH THE SYSTEM INSTALLER FOR ADDITIONAL INFORMATION.
- 5. PROVIDE ONE 3" EMPTY CONDUIT W/PULL STRING FROM BUILDING SERVICE ENTRANCE TO EACH RETAIL SPACE, ROUTED OVERHEAD AND STUBBED INTO CEILING SPACE AND CAPPED AT BOTH ENDS FOR FUTURE TENANT'S SERVICE. SUCH SERVICE SHALL BE CONNECTED AS PART OF THE TENANT'S IMPROVEMENTS. CONSULT ARCHITECT AND/OR OWNER TO DETERMINE BEST LOCATION PRIOR TO ROUGH IN.
- 6. PROVIDE AND INSTALL OVERHEAD DOOR OPENER. FINAL CONNECTION SHALL BE MADE BY TENANT.
- 7. PROVIDE 120V TWIST TIMER SWITCH (MAX. 60 MINUTES, "NO HOLD") IN WEATHER PROOF BOX FOR GAS GRILL AND FIRE PIT IGNITER CONTROLS. CIRCUIT FROM PANEL H2.
- 8. PROVIDE EMERGENCY SHUTOFF CONTROLS FOR GAS APPLIANCES LOCATED ON TERRACE. COORDINATE INSTALLATION WITH MECHANICAL CONTRACTOR. SEE DETAIL 5/E1.22 FOR EMERGENCY SHUT-OFF DIAGRAM. CIRCUIT FROM PANEL H2.
- 9. REFER TO MECHANICAL PLANS FOR GRILL HOOD INFORMATION AND PROVIDE ELECTRICAL CONNECTIONS AS REQUIRED. SEE E3.05 FOR EXHAUST FAN LOCATION.

KEYED APARTMENT NOTES:

- 1. PROVIDE WIRE CONNECTION FOR THERMOSTAT(S). COORDINATE WITH MECHANICAL INSTALLER FOR EXACT LOCATION AND POWER REQUIREMENTS PRIOR TO ROUGH IN. THERMOSTATS TO BE MOUNTED AT 48" AFF MAX. TO HIGHEST OPERABLE PART.
- 2. PROVIDE ONE 20A, 120V, 1P GFCI DUPLEX RECEPTACLE UNDER KITCHEN SINK FOR DISPOSAL POWER CONNECTION. DISPOSAL TO BE PROVIDED WITH "SAFEAIRE" SINK DISPOSAL AIR SWITCH, MOUNTED PER ARCHITECT'S DIRECTION. VERIFY DEVICE FINISH WITH ARCHITECT PRIOR TO ORDERING.
- 3. PROVIDE ONE 15A SPLIT BUSS SWITCHED RECEPTACLE. REFER TO LIGHTING PLANS FOR SWITCH LOCATION.
- 4. PROVIDE ONE 15A, RECEPTACLE CIRCUIT FROM TENANT LOAD CENTER FOR TELECOM SMART PANEL. COORDINATE WORK WITH SERVICE PROVIDER FOR EXACT LOCATION AND FINAL CONNECTION.
- 5. FOR RANGE HOODS/MICROWAVES PROVIDED WITH A CORD & PLUG SET, PROVIDE A 20A DUPLEX RECEPTACLE LOCATED INSIDE THE OVERHEAD CABINET. HARDWIRED APPLIANCES MAY BE CIRCUITED VIA J-BOX MOUNTED FLUSH OR RECESSED INTO THE WALL DIRECTLY BEHIND THE APPLIANCE.
- 6. REFER TO SHEET E1.21 FOR TYPICAL BATHROOM SWITCHING DIAGRAM.
- 7. REFER TO SHEET E1.22 FOR TYPICAL LAUNDRY ALCOVE DETAIL.

APPLIANCE CIRCUITS

- | | |
|----------------------|--------------------------|
| 1. REFRIGERATOR LC-6 | 5. DISPOSAL LC-16 |
| 2. MICRO/HOOD LC-8 | 6. WASHER LC-13 |
| 3. RANGE LC-10,12 | 7. DRYER LC-15,17 |
| 4. DISHWASHER LC-14 | 8. SMART PNL LC-23 (OPT) |

M
F
I
A
INC. Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR




EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022

REVISIONS

SHEET:



1 FOURTH FLOOR POWER PLAN
E3.04 SCALE: 1/8" = 1'-0"

GENERAL POWER NOTES:

- ALL PLANS ARE CONSIDERED DIAGRAMMATICAL. THEREFORE ALL EQUIPMENT SIZES AND DEVICE LOCATIONS ARE APPROXIMATE AND SUBJECT TO FIELD CONDITIONS AND PRODUCT APPROVAL.
- ELECTRICAL EQUIPMENT SHOWN ON THE PLANS IS APPROXIMATE, BASED ON STANDARD PRODUCTS. CONTRACTOR SHALL VERIFY ANY SUBMITTED EQUIPMENT WILL FIT WITHIN THE SPACE PROVIDED, PRIOR TO PRODUCT SUBMITTAL REVIEW.
- GENERAL PURPOSE CONVENIENCE RECEPTACLES LOCATED ON THE BUILDING EXTERIOR, OTHER THAN INTERIOR COURT YARD, SHALL BE EQUIPPED WITH A LOCKING, WEATHER PROOF COVER.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO VERIFY EXACT LOCATIONS AND FINISHES FOR LIGHT FIXTURES AND DEVICES.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE CIVIL ENGINEER, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE MECHANICAL AND PLUMBING CONTRACTORS, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LANDSCAPING CONTRACTOR, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE ('T' SERIES) PLANS, INCLUDING FIRE ALARM AND SYSTEMS INSTALLER, AND PROVIDE ROUGH IN AS NEEDED.
- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING THE ELECTRICAL PLANS AND ALL OTHER SUPPORTING DOCUMENTS PRIOR TO THE START OF ANY WORK. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION UPON DISCOVERY.
- ALL LIGHTING, DEVICES AND HVAC EQUIPMENT LOCATED IN THE RETAIL TENANT SPACES IS CONSIDERED TEMPORARY AND SHALL BE REMOVED AND/OR DISCONNECTED FROM THE HOUSE POWER AT THE TIME OF THE TENANT'S SPACE IMPROVEMENT WORK.

KEYED NOTES:

- VERIFY ELEVATOR EQUIPMENT LOCATION AND ELECTRICAL REQUIREMENTS WITH ARCHITECT AND/OR ELEVATOR PROVIDER.
- PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR AUTOMATIC DOOR OPENERS.
- LOW VOLTAGE/COMMUNICATIONS SYSTEM DEMARCATION BOARD(S). COORDINATE LOCATIONS AND ELECTRICAL POWER REQUIREMENTS WITH THE TELECOM AND LOW VOLTAGE SYSTEMS INSTALLER(S). PROVIDE ROUGH IN AND/OR FINAL ELECTRICAL POWER CONNECTIONS. REFER PANEL 'H1' SCHEDULE ON E1.12 FOR RESERVED CIRCUITS.
- PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR BUILDING ENTRY ACCESS CONTROL SYSTEM AND PROVIDE ROUGH IN AND WIRING TO ACCESS POINTS AS DETERMINED BY OWNER AND/OR ARCHITECT. CONSULT WITH THE SYSTEM INSTALLER FOR ADDITIONAL INFORMATION.
- PROVIDE ONE 3" EMPTY CONDUIT W/PULL STRING FROM BUILDING SERVICE ENTRANCE TO EACH RETAIL SPACE, ROUTED OVERHEAD AND STUBBED INTO CEILING SPACE AND CAPPED AT BOTH ENDS FOR FUTURE TENANT'S SERVICE. SUCH SERVICE SHALL BE CONNECTED AS PART OF THE TENANT'S IMPROVEMENTS. CONSULT ARCHITECT AND/OR OWNER TO DETERMINE BEST LOCATION PRIOR TO ROUGH IN.
- PROVIDE AND INSTALL OVERHEAD DOOR OPENER. FINAL CONNECTION SHALL BE MADE BY TENANT.
- PROVIDE 120V TWIST TIMER SWITCH (MAX. 60 MINUTES, "NO HOLD") IN WEATHER PROOF BOX FOR GAS GRILL AND FIRE PIT IGNITER CONTROLS. CIRCUIT FROM PANEL H2.
- PROVIDE EMERGENCY SHUTOFF CONTROLS FOR GAS APPLIANCES LOCATED ON TERRACE. COORDINATE INSTALLATION WITH MECHANICAL CONTRACTOR. SEE DETAIL 5/E1.22 FOR EMERGENCY SHUT-OFF DIAGRAM. CIRCUIT FROM PANEL H2.
- REFER TO MECHANICAL PLANS FOR GRILL HOOD INFORMATION AND PROVIDE ELECTRICAL CONNECTIONS AS REQUIRED. SEE E3.05 FOR EXHAUST FAN LOCATION.

KEYED APARTMENT NOTES:

- PROVIDE WIRE CONNECTION FOR THERMOSTAT(S). COORDINATE WITH MECHANICAL INSTALLER FOR EXACT LOCATION AND POWER REQUIREMENTS PRIOR TO ROUGH IN. THERMOSTATS TO BE MOUNTED AT 48" AFF MAX. TO HIGHEST OPERABLE PART.
- PROVIDE ONE 20A, 120V, 1P GFIC DUPLEX RECEPTACLE UNDER KITCHEN SINK FOR DISPOSAL POWER CONNECTION. DISPOSAL TO BE PROVIDED WITH "SAFEAIRE" SINK DISPOSAL AIR SWITCH, MOUNTED PER ARCHITECT'S DIRECTION. VERIFY DEVICE FINISH WITH ARCHITECT PRIOR TO ORDERING.
- PROVIDE ONE 15A SPLIT BUSS SWITCHED RECEPTACLE. REFER TO LIGHTING PLANS FOR SWITCH LOCATION.
- PROVIDE ONE 15A, RECEPTACLE CIRCUIT FROM TENANT LOAD CENTER FOR TELECOM SMART PANEL. COORDINATE WORK WITH SERVICE PROVIDER FOR EXACT LOCATION AND FINAL CONNECTION.
- FOR RANGE HOODS/MICROWAVES PROVIDED WITH A CORD & PLUG SET, PROVIDE A 20A DUPLEX RECEPTACLE LOCATED INSIDE THE OVERHEAD CABINET. HARDWIRED APPLIANCES MAY BE CIRCUITED VIA J-BOX MOUNTED FLUSH OR RECESSED INTO THE WALL DIRECTLY BEHIND THE APPLIANCE.
- REFER TO SHEET E1.21 FOR TYPICAL BATHROOM SWITCHING DIAGRAM.
- REFER TO SHEET E1.22 FOR TYPICAL LAUNDRY ALCOVE DETAIL.

APPLIANCE CIRCUITS

- | | |
|----------------------|--------------------------|
| 1. REFRIGERATOR LC-6 | 5. DISPOSAL LC-16 |
| 2. MICRO/HOOD LC-8 | 6. WASHER LC-13 |
| 3. RANGE LC-10,12 | 7. DRYER LC-15,17 |
| 4. DISHWASHER LC-14 | 8. SMART PNL LC-23 (OPT) |

STUDIO

3

ARCHITECTURE
INCORPORATED

275 COURT ST. NE
SALEM, OR 97301-3442
P: 503.390.6500
www.studio3architecture.com



EXPIRES: July 5th, 2022

IN THE EVENT CONFLICTS ARE DISCOVERED BETWEEN THE ORIGINAL SIGNED AND SEALED DOCUMENTS PREPARED BY THE ARCHITECTS AND/OR THEIR CONSULTANTS, AND ANY COPY OF THE DOCUMENTS TRANSMITTED BY MAIL, FAX, ELECTRONICALLY OR OTHERWISE, THE ORIGINAL SIGNED AND SEALED DOCUMENTS SHALL GOVERN.

PROJECT # 2019-149
DATE: 05/20/2022


REVISIONS

MULTI-FAMILY DEVELOPMENT
DAYBREAK STATION
1806 NW 1st WAY, BATTLEGROUND WA

SHEET:

E3.04

MFA Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR



1 ROOF LEVEL POWER PLAN
E3.05 SCALE: 1/8" = 1'-0"

GENERAL POWER NOTES:

- ALL PLANS ARE CONSIDERED DIAGRAMMATICAL. THEREFORE ALL EQUIPMENT SIZES AND DEVICE LOCATIONS ARE APPROXIMATE AND SUBJECT TO FIELD CONDITIONS AND PRODUCT APPROVAL.
- ELECTRICAL EQUIPMENT SHOWN ON THE PLANS IS APPROXIMATE, BASED ON STANDARD PRODUCTS. CONTRACTOR SHALL VERIFY ANY SUBMITTED EQUIPMENT WILL FIT WITHIN THE SPACE PROVIDED, PRIOR TO PRODUCT SUBMITTAL REVIEW.
- GENERAL PURPOSE CONVENIENCE RECEPTACLES LOCATED ON THE BUILDING EXTERIOR, OTHER THAN INTERIOR COURT YARD, SHALL BE EQUIPPED WITH A LOCKING, WEATHER PROOF COVER.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE ARCHITECT TO VERIFY EXACT LOCATIONS AND FINISHES FOR LIGHT FIXTURES AND DEVICES.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE CIVIL ENGINEER, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE MECHANICAL AND PLUMBING CONTRACTORS, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LANDSCAPING CONTRACTOR, TO VERIFY EXACT POWER REQUIREMENTS, LOCATIONS AND CONNECTION TYPE FOR ANY EQUIPMENT REQUIRING ELECTRICAL POWER, PRIOR TO ROUGH IN.
- ELECTRICAL CONTRACTOR SHALL COORDINATE WITH THE LOW VOLTAGE ('T' SERIES) PLANS, INCLUDING FIRE ALARM AND SYSTEMS INSTALLER, AND PROVIDE ROUGH IN AS NEEDED.
- ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING THE ELECTRICAL PLANS AND ALL OTHER SUPPORTING DOCUMENTS PRIOR TO THE START OF ANY WORK. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ARCHITECT'S ATTENTION UPON DISCOVERY.
- ALL LIGHTING, DEVICES AND HVAC EQUIPMENT LOCATED IN THE RETAIL TENANT SPACES IS CONSIDERED TEMPORARY AND SHALL BE REMOVED AND/OR DISCONNECTED FROM THE HOUSE POWER AT THE TIME OF THE TENANT'S SPACE IMPROVEMENT WORK.

KEYED NOTES:

- VERIFY ELEVATOR EQUIPMENT LOCATION AND ELECTRICAL REQUIREMENTS WITH ARCHITECT AND/OR ELEVATOR PROVIDER.
- PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR AUTOMATIC DOOR OPENERS.
- LOW VOLTAGE/COMMUNICATIONS SYSTEM DEMARCATION BOARD(S). COORDINATE LOCATIONS AND ELECTRICAL POWER REQUIREMENTS WITH THE TELECOM AND LOW VOLTAGE SYSTEMS INSTALLER(S). PROVIDE ROUGH IN AND/OR FINAL ELECTRICAL POWER CONNECTIONS. REFER PANEL 'H1' SCHEDULE ON E1.12 FOR RESERVED CIRCUITS.
- PROVIDE ONE 20A, 120V, 1P CIRCUIT FROM PANEL H1 FOR BUILDING ENTRY ACCESS CONTROL SYSTEM AND PROVIDE ROUGH IN AND WIRING TO ACCESS POINTS AS DETERMINED BY OWNER AND/OR ARCHITECT. CONSULT WITH THE SYSTEM INSTALLER FOR ADDITIONAL INFORMATION.
- PROVIDE ONE 3" EMPTY CONDUIT W/PULL STRING FROM BUILDING SERVICE ENTRANCE TO EACH RETAIL SPACE, ROUTED OVERHEAD AND STUBBED INTO CEILING SPACE AND CAPPED AT BOTH ENDS FOR FUTURE TENANT'S SERVICE. SUCH SERVICE SHALL BE CONNECTED AS PART OF THE TENANT'S IMPROVEMENTS. CONSULT ARCHITECT AND/OR OWNER TO DETERMINE BEST LOCATION PRIOR TO ROUGH IN.
- PROVIDE AND INSTALL OVERHEAD DOOR OPENER. FINAL CONNECTION SHALL BE MADE BY TENANT.
- PROVIDE 120V TWIST TIMER SWITCH (MAX. 60 MINUTES, "NO HOLD") IN WEATHER PROOF BOX FOR GAS GRILL AND FIRE PIT IGNITER CONTROLS. CIRCUIT FROM PANEL H2.
- PROVIDE EMERGENCY SHUTOFF CONTROLS FOR GAS APPLIANCES LOCATED ON TERRACE. COORDINATE INSTALLATION WITH MECHANICAL CONTRACTOR. SEE DETAIL 5/E1.22 FOR EMERGENCY SHUT-OFF DIAGRAM. CIRCUIT FROM PANEL H2.
- REFER TO MECHANICAL PLANS FOR GRILL HOOD INFORMATION AND PROVIDE ELECTRICAL CONNECTIONS AS REQUIRED. SEE E3.05 FOR EXHAUST FAN LOCATION.

KEYED APARTMENT NOTES:

- PROVIDE WIRE CONNECTION FOR THERMOSTAT(S). COORDINATE WITH MECHANICAL INSTALLER FOR EXACT LOCATION AND POWER REQUIREMENTS PRIOR TO ROUGH IN. THERMOSTATS TO BE MOUNTED AT 48" AFF MAX. TO HIGHEST OPERABLE PART.
- PROVIDE ONE 20A, 120V, 1P GFIC DUPLEX RECEPTACLE UNDER KITCHEN SINK FOR DISPOSAL POWER CONNECTION. DISPOSAL TO BE PROVIDED WITH "SAFEAIRE" SINK DISPOSAL AIR SWITCH, MOUNTED PER ARCHITECT'S DIRECTION. VERIFY DEVICE FINISH WITH ARCHITECT PRIOR TO ORDERING.
- PROVIDE ONE 15A SPLIT BUSS SWITCHED RECEPTACLE. REFER TO LIGHTING PLANS FOR SWITCH LOCATION.
- PROVIDE ONE 15A, RECEPTACLE CIRCUIT FROM TENANT LOAD CENTER FOR TELECOM SMART PANEL. COORDINATE WORK WITH SERVICE PROVIDER FOR EXACT LOCATION AND FINAL CONNECTION.
- FOR RANGE HOODS/MICROWAVES PROVIDED WITH A CORD & PLUG SET, PROVIDE A 20A DUPLEX RECEPTACLE LOCATED INSIDE THE OVERHEAD CABINET. HARDWIRED APPLIANCES MAY BE CIRCUITED VIA J-BOX MOUNTED FLUSH OR RECESSED INTO THE WALL DIRECTLY BEHIND THE APPLIANCE.
- REFER TO SHEET E1.21 FOR TYPICAL BATHROOM SWITCHING DIAGRAM.
- REFER TO SHEET E1.22 FOR TYPICAL LAUNDRY ALCOVE DETAIL.

APPLIANCE CIRCUITS

- | | |
|----------------------|--------------------------|
| 1. REFRIGERATOR LC-6 | 5. DISPOSAL LC-16 |
| 2. MICRO/HOOD LC-8 | 6. WASHER LC-13 |
| 3. RANGE LC-10,12 | 7. DRYER LC-15,17 |
| 4. DISHWASHER LC-14 | 8. SMART PNL LC-23 (OPT) |

M
F
I
A
INC.
Consulting Engineers
2007 S.E. Ash St.
Portland, OR 97214
PHN: (503) 234-0548
FAX: (503) 234-0877
CONTACT: DENISE TAYLOR