



3 TELCOM CABLING DETAIL
T1.21 N.T.S.

GENERAL NOTES:

- A. ROUTE CABLING FROM INTERMEDIATE DISTRIBUTION POINTS AND SMART PANELS PER UTILITY REQUIREMENTS. FOLLOW ALL INDUSTRY STANDARDS FOR PULLING TENSION, BEND RADIUS, AND METHODS OF SUPPORT.
- B. PROVIDE CONDUIT SLEEVES BETWEEN FLOORS AS NEEDED AND A SPARE 4" SLEEVE BETWEEN FLOORS.
- C. PROVIDE REQUIRED PHONE OUTLETS FOR FIRE ALARM AND ELEVATOR.
- D. PERFORM TESTS FOR WIRE MAP, LENGTH, ATTENUATION, NEXT, AND PROPAGATION DELAY FOR CATEGORY 5e LINKS.
- E. THE CONTRACTOR SHALL COMPILE TEST RESULTS INTO FORMS THAT CONTAIN ALL APPLICABLE TEST DATA. ALL FORMS SHALL BE NEATLY COMPLETED AND LEGIBLE WHEN SUBMITTED.

KEYED NOTES:

- 1. RF TRANSPARENT MEDIA PANEL: 42"H X 14"W X 5"D PRIMEX PART# P4200ND SOHO PRO (NARROW/DEEP)
- 2. PROVIDE PHONE BOARD OR BOARDS AS NEEDED. CONTRACTOR MAY ADD INTERMEDIATE BOARDS IF LOCATIONS ARE APPROVED BY ARCHITECT AND TRUNK CABLE(S) AND CONNECTIONS ARE PROVIDED.
- 3. PROVIDE (2) RJ-45 JACK AND (1) F-CONNECTOR RG-6 COAXIAL IN A 3-PORT FACEPLATE COLORS AS SELECTED BY ARCHITECT
- 4. (2) 2" CONDUITS TO ROOF FOR POSSIBLE FUTURE 'DAS' SYSTEM.